

CyberPower PR3000ERTXL2U uninterruptible power supply (UPS) Line-Interactive 3 kVA 3000 W 8 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **PR3000ERTXL2U** · EAN: **4712856277579** · Prekės kodas: **345211**



1 786,90 €

Kaina su PVM

Be PVM: **1 476,78 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Reliable Power Quality
- ✓ Electricity Cost Savings
- ✓ Device Protection Design
- ✓ Automatic Voltage Regulation (AVR)
- ✓ Real-time LCD Readout



Aprašymas

CyberPower PR3000ERTXL2U with rackmount design guarantees power backup protection for home theater systems, multimedia devices, IT equipment, computers, workstations, NAS/Storage devices, telecom devices, networking devices, and surveillance systems. The UPS adopts line-interactive topology with Automatic Voltage Regulation (AVR) function, and offers stabilized Pure Sine Wave output to ensure high power quality.

The UPS's output power factor is 1, which means it is capable of connecting to more critical loads than conventional UPS. It also features Battery Management Technology to help batteries obtain optimal life span by balancing battery string voltage. Two-phase battery charging can charge the battery quickly and safely. The hot-swappable battery packs allow for easy maintenance without power interruption. Its multi-functional matrix LCD supports intuitive operation and quick configuration. The LCD panel is also rotatable to meet installation requirements.

Techninė specifikacija

Specifications	
Sandėlio grupė	Peripherals, consumables, UPS > UPS [+0][-0]
Features	
UPS topology	Line-Interactive
Output power capacity	3 kVA
Output power	3000 W
Waveform	Pure sine
Input operation voltage (min)	159 V
Input operation voltage (max)	288 V
Input frequency	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Maximum current	16 A
Surge energy rating	2430 J
Transfer time (Line Mode to Battery Mode)	4 ms
Response time	4 ms
Number of input phases	1
Power factor	1
Power Factor Correction (PFC) type	Active
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Overload, Short circuit
Audible alarm(s)	Yes
Web-based management	Yes
Management protocols	SNMP/HTTP
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Socket circuit breaker	Yes
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler
Power plug	C20 coupler
AC outlets quantity	8 AC outlet(s)

USB port	Yes
Serial interface	Yes
Serial interface type	RS-232
Ethernet LAN (RJ-45) ports	2
Cabling technology	10/100/1000Base-T(X)
Emergency Power Off (EPO) connector	Yes
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	4
Typical backup time at full load	1.7 min
Typical backup time at half load	7.1 min
Battery recharge time	3 h
Hot-swap battery	Yes
Replacement battery cartridge	RBP0129
Design	
Form factor	Rackmount/Tower
Product colour	Black
Housing material	Metal
Rack capacity	2U
Cable length	2.4 m
Display type	LCD
LED indicators	Error, Operation
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Certificates	
Compliance certificates	RoHS
Certification	CE , FCC Class A , UL , CISPR 22 Class A , IEC62040-2 , RCM , VCCI , EN 61000-3-2
Sustainability	
Sustainability certificates	ENERGY STAR

Weight & dimensions

Width	433 mm
Depth	500 mm
Height	86.5 mm
Weight	32.8 kg

Packaging data

Package width	560 mm
Package depth	620 mm
Package height	275 mm
Package weight	41 kg
Package volume	40800 cm ³

Logistics data

Harmonized System (HS) code	8504408590
Country of origin	China

Other features

Bypass	GreenPower UPS
--------	----------------

Matmenys ir svoris

Matmenys (I × P × A)	62,00cm × 56,00cm × 28,00cm
Svoris	40,80kg