Axagon ADE-SRC tinklo plokštė Eternetas 1000 Mbit/ai

Gamintojas: **AXAGON** · Modelis: **ADE-SRC** · EAN: **8595247903785** · Prekės kodas: **346789**



15,90 €

Kaina su PVM

Be PVM: **13,14 €**

Sandėlyje


Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės


- ✓ Vielinis
- ✓ C tipo USB 2.0/3.2 Gen 1 (3.1 Gen 1) Eternetas
- ✓ Greitas eternetas, Gigabitinis eternetas 1000 Mbit/ai
- ✓ Taikoma: Kompiuteris / knyginis kompiuteris Lustų rinkinys: Realtek RTL8153










Aprašymas

The compact super-speed AXAGON ADE-SRC adapter easily converts USB-C 3.1 Gen 1 port to Gigabit Ethernet 10/100/1000 Mbit port.

In addition to a Gigabit bandwidth, the network card offers a wide range of features, such as IPv4/IPv6 checksum to reduce CPU loading by checksums, the crossover detection and auto-correction, TCP large send offload, support for various modes of the Wake-on-LAN feature, the work with virtual LAN (VLAN) and advanced Power Management features.

In modern operating systems from Windows 8.1 above, the adapter allows easy automatic installation without the need for an Internet connection.

Gigabit network card extends your computer by a fast network connection, adds the missing RJ-45 network connector or another network card, or replaces the original defunct network connection.

The support for current versions of Windows, Mac OS X, and Linux operating systems allows it to be used for any desktop, laptop or ultrabook equipped with a modern two-sided USB Type C connector. Also, some Android phones and tablets, such as the Samsung S9+, can be easily connected to the Internet with a network Ethernet cable thanks to this adapter.

Input:
• Interface USB 3.1 gen 1 / USB 3.0, backward compatible with USB 2.0 and USB 1.1.
• Supports transmission rates 12 / 480 / 5000 Mb/s (low / full / high speed).
• Connecting USB Type C male connector on a 15 cm long cable permanently attached to the adapter.

Output:
• Gigabit Ethernet interface with RJ-45 connector for UTP or STP cable connection.
• Supported transmission rates for the Ethernet interface 10/100/1000 Mb/s.
• Supported IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T specifications.
• 10/100/1000 Mbit/s auto-detection.
• Supports IPv4 / IPv6 packet Checksum Offload Engine (COE) to reduce processor load, including IPv4 IP/TCP/UDP/ICMP/ IGMP & IPv6 TCP/UDP/ICMPv6 checksum control and generation.
• Supports TCP Large Send Offload V1 and V2.
• Supports IEEE 802.1P Layer 2 priority encoding & decoding.
• Supports IEEE 802.1Q VLAN tagging.
• Supports IEEE 802.3az EEE (Energy Efficient Ethernet) - reduce power consumption at rest.
• Supports Jumbo frame.
• Supports full-duplex transmissions with IEEE 802.3x flow control and half-duplex transmissions with back-pressure flow control.
• Supports Auto MDI/MDIX - crossover detection and auto-correction eliminates the need for crossover cables.
• Supports hardware Cyclic Redundancy Check (CRC) to detect transmission errors.
• Supports Pair Swap/Polarity/Skew Correction.

Other features:
• Full Plug and Play and Hot Plug support.
• Supports CDC-ECM – for automatic installation of drivers across different OSs.
• Adapter power supply via USB (bus power) - no auxiliary power supply required.
• Two LEDs to indicate the network activity and to connect the adapter to the USB and network.
• Dimensions 61 x 25 x 17 mm, USB cable length 15 cm, weight incl. USB cable 23 g.
• The Realtek RTL8153 chipset is used.

Supports Wake-on-LAN feature in different modes:
• Supports sleep mode and remote Wake Up via Magic Packet, Microsoft Wakeup Frame, Microsoft Wake Packet Detection and Link Change Wake-up.
• Supports ECMA-393 proxZzzy® standard for sleeping hosts to manage the network connection of sleeping guests using proxy servers.

• RealWoW! technology support allows remote wake up over the Internet.

Advanced Power Management features:
The adapter supports advanced power management to reduce losses during standby or light traffic on the network. It further supports advanced power saving when the Ethernet cable has been disconnected.
• Supports Advanced Configuration Power Management Interface (ACPI).
• Supports Power Management offload (ARP & NS).
• Supports Microsoft Always On Always Connected (AOAC).
• Supports Intel Converged Platform Power Management (CPPM).
• Supports Link Power Management (LPM).
• Supports Operating System-directed Power Management (OSPM).
• Supports IEEE 802.3az EEE (Energy Efficient Ethernet).

Supported OSs:
• MS Windows XP / Vista / 7 / 8 / 8.1 / 10 and later, Windows Server 2003 / 2008 / 2012 / 2016 and later (supported are all 32 and 64-bit versions of Windows OSs),
• MacOS X 10.6 and higher,
• Linux with kernel 2.6.14 and above,
• Android most versions (WARNING - check with the Android device manufacturer if the Ethernet connection is supported).

Package contains:
• USB - Gigabit Ethernet adapter with a 15 cm long permanently attached cable,
• printed installation manual CZ/DE/ENG/ESP/FR/HU/IT/PL/RO/RU/SK,
• packed in a cardboard box with a hole for easy hanging from a sales stand.

Techninė specifikacija

Ryšys	
Ryšio technologija	Vielinis
Priimančioji sąsaja	C tipo USB
Sąsaja	Eternetas
Ethernet LAN (RJ-45) portų kiekis	1
USB versija	2.0/3.2 Gen 1 (3.1 Gen 1)
Tinklas	
Didžiausias duomenų perdavimo greitis	1000 Mbit/ai
Tinklo standartai	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Ethernet LAN jungtis	Taip
Eterneto sąsajos tipas	Greitas eternetas, Gigabitinis eternetas
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Wake-on-LAN pasirengimas	Taip
Pilnai abipusis (duplex)	Taip
Jumbo Frames palaikymas	Taip
VLAN palaikymas	Taip

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

LAN kontroleris	Realtek RTL8153
Konstrukcija	
Vidinis	Ne
Taikoma	Kompiuteris / knyginis kompiuteris
Produkto spalva	Juoda
Lustų rinkinys	Realtek RTL8153
„Plug and Play“ funkcija	Taip
LED indikatoriai	Taip
Kilmės šalis	Kinija
Sertifikavimas	CE, RoHS
Energijos valdymas	
USB maitinimas	Taip
Sistemos reikalavimai	
Palaikomos „Windows“ operacinės sistemos	Taip
Palaikomos MAC operacinės sistemos	Taip
Palaikoma operacinė sistema „Linux“	Taip
Palaikomos serverio valdymo sistemos	Taip
Svoris ir matmenys	
Plotis	61 mm
Ilgis	25 mm
Aukštis	17 mm
Svoris	23 g
Pakuotės duomenys	
Pakuotės plotis	180 mm
Pakuotės gylis	90 mm
Pakuotės aukštis	25 mm
Paketo svoris	54 g
Pakuotės turinys	
Instrukcija	Taip
Techninė informacija	
Garantinis laikotarpis	3 metai
Atitikties sertifikatai	RoHS, CE
Kitos savybės	
Duomenų perdavimo sparta	5 Gbit/s

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Kabelio ilgis	0,15 m
Matmenys ir svoris	
Matmenys (I × P × A)	3,00cm × 9,00cm × 18,00cm
Svoris	0,05kg

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.