



## EcoFlow Alternator Charger



Modelis: 5015501001

Gamintojas: ECOFLOW

EAN: 4895251623230

Prekės kodas: 352405

# 353.99€

### EcoFlow Alternator Car Charger

The EcoFlow Alternator Charger Car Charger offers up to 800 watts of charging power on the go and the ability to charge 1kWh in only 75 minutes, revolutionizing the way we travel by car. Connecting to the vehicle's alternator, it efficiently uses excess energy, providing a reliable power source for various types of vehicles. With various modes of operation and a comprehensive safety guarantee, it guarantees peace of mind on the road.

### A new dimension of power on the road

With the unique ability to generate up to 800W of power and quickly charge 1kWh in just 75 minutes, this innovative charger is a game changer in travel. Connecting to the vehicle's alternator, it transforms excess power into practical solutions, not just meeting the car's electrical needs. With a built-in DC-DC converter, you can efficiently charge EcoFlow portable power stations and increase the capacity of your existing RV battery by up to 7.2 kWh. Adapting to 12V/24V RV batteries, the

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

EcoFlow charger guarantees a reliable power source anywhere, anytime, regardless of the type of RV.

## Choose from available operating modes

The EcoFlow Alternator Charger offers a range of operating modes to provide versatile support in any situation. With Charge Mode, you'll use excess power from the alternator, effectively charging the power station. The reverse charge mode (Jump Start) becomes a lifesaver when your vehicle's battery weakens, allowing you to start the engine quickly. In addition, the battery maintenance mode will allow you to prolong the life of your vehicle's battery by using a small reverse current to maintain its ability, which will be especially useful when parking.

## Safety first

Using advanced gallium nitride (GaN) technology, the EcoFlow charger provides thermal resistance and high performance even under extreme conditions. Reverse polarity, overcurrent and short-circuit protection take care of your devices and vehicle, eliminating the risk of unwanted failures. Built-in overvoltage and under-voltage protection gives you peace of mind that your equipment is safe even in the event of sudden power changes. With simple installation in 6 steps, using the EcoFlow Alternator Charger becomes not only easy and convenient, but most importantly, it provides complete peace of mind and safety on the road.

## Included:

- car charger
- 5 m input cable
- XT150 output cable 1 m
- fuse cable
- installation plate
- screws and dowels (M5 x12, ST5 x 25, M5 x 40, M6 x 20)
- M6 nuts
- cable stripper
- instruction manual

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

<b>Manufacturer</b>	EcoFlow
<b>Model</b>	5015501001
<b>Net weight</b>	2.3 kg
<b>Dimensions (W x D x H)</b>	242 × 194 × 35 mm
<b>Wi-Fi frequency</b>	2412 MHz - 2472 MHz
<b>Maximum WiFi output power</b>	20dBm
<b>Bluetooth frequency</b>	2402 MHz - 2480 MHz
<b>Maximum Bluetooth output power</b>	10 dBm
<b>Charging mode</b>	Input: 11V-35V, 76A max; Output: 40V-60V, 500W Max.
<b>Battery maintenance mode</b>	input: 40V-60V, 3A max; output: 13.8V/27.6V, 100W max.
<b>Reverse charging mode</b>	input: 40V-60V, 21A max; output: 13.8V/27.6V, 800W max.
<b>Rated fuse current</b>	125 A
<b>Protection</b>	Reverse polarity protection; overcurrent protection, short-circuit protection, overvoltage and under-voltage protection
<b>Operating temperature</b>	-20°C to 60°C
<b>Storage temperature</b>	-30°C to 70°C
<b>Operating humidity</b>	≤95%
<b>Storage humidity</b>	≤95%

Net weight: 2300, Box length: 24,20, Box width: 19,40, Box height: 3,50, Gross weight: 6000, Last delivery: 20.03.2026, Rodzaje portów: Inne, GPSR Link: [https://psr-assets.innpro.pl/gsm\\_accessories/sg\\_gsm\\_accessories\\_chargers.pdf](https://psr-assets.innpro.pl/gsm_accessories/sg_gsm_accessories_chargers.pdf), test: Ładowarka Samochodowa EcoFlow Alternator Charger 800W, Information about data generation: <https://dataact.innpro.pl/ecoflow/4895251623230>

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903