



**HDD WESTERN
DIGITAL
ULTRASTAR
Ultrastar DC
HC310
HUS726T4TALE6L4
4TB SATA 3.0
256 MB 7200
rpm 3,5
0B36040**

Modelis: 0B36040

Gamintojas: WESTERN DIGITAL ULTRASTAR

Prekės kodas: 353055

246.99€

Delivering Economics and Access Speed to Data Center Applications and Workloads

As the industry evolves to develop purpose-built solutions for growing data storage requirements, IT managers continue to rely on mid-range capacity drives that are economical to acquire, yet deliver

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

quick and reliable data access for traditional data center applications. Designed to handle workloads up to 550TB per year, the Ultrastar DC HC300 series is a proven air-filled design that delivers up to the industry leading 10TB1 of capacity to help address the economic and access-density requirements of many data center workloads. Ideal for storage and server applications, as well as distributed and scalable computing (including block and file storage architectures), the Ultrastar DC HC300 series provides fast 7,200 RPM spindle speeds and is offered in either 6Gb/s SATA or 12Gb/s SAS interface with advanced format 512e2 sector size.

- 4TB-10TB capacities support both OEM & Cloud deployments
- Common Hardware & Firmware to minimize redundant testing needs
- Advanced Format 512e models
- Self-encrypting drive options

Summary: Western Digital Ultrastar DC HC310 HUS726T4TALE6L4. HDD capacity: 4 TB, HDD speed: 7200 RPM, Storage drive buffer size: 256 MB, HDD size: 3.5", Interface: Serial ATA III | Vendor Homepage: <https://www.westerndigital.com/products/data-center-platforms/ultrastar-dc-hc300-series-hdd> | Average latency: 4.16 | Component for: Server/workstation | HDD capacity: 4000 | HDD interface transfer rate: 6 | HDD size: 3.5 | HDD speed: 7200 | Interface: Serial ATA III | Mean time between failures (MTBF): 2000000 | Read seek time: 8 | Start/stop cycles: 600000 | Storage drive buffer size: 256 | Type: HDD | Write seek time: 8.6 | Operating voltage: 5 / 12 | Power consumption (idle): 5.9 | Power consumption (typical): 7 | Non-operating shock: 300 | Non-operating vibration: 1.04 | Operating shock: 70 | Operating temperature (T-T): 5 - 60 | Operating vibration: 0.67 | Storage temperature (T-T): -40 - 70 | Depth: 147 | Height: 26.1 | Weight: 715 | Width: 101.6 | Quantity per pack: 1 | Harmonized System (HS) code: 84717050 | HDD Family name: Ultrastar DC HC310 | Model name: HUS726T4TALE6L4 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.0003625 | Product Net Weight: 0.715 | Unit Calculated Weight: 0.72