

WRL ROUTER 5G OUTDOOR/OTD500 TELTONIKA



Modelis: OTD500

Gamintojas: TELTONIKA

EAN: 4779051842933

Prekės kodas: 356925

477.99€

Teltonika OTD500 - Advanced 5G Router for Your Business and Home

The Teltonika OTD500 is a state-of-the-art 5G router that delivers incredible performance, stability and functionality. With support for LTE Cat 19, eSIM, PoE in/out, and IP55 immunity, this router is perfect for both demanding business environments and home applications. Whether you're looking for a stable Internet connection for IoT or an advanced monitoring and remote management solution, the Teltonika OTD500 will meet your needs.

Latest 5G and LTE Cat 19 technology

The Teltonika OTD500 supports 5G Sub-6Ghz SA/NSA, which means ultra-fast download speeds of up to 3.4 Gbps and upload speeds of up to 900 Mbps. With LTE Cat 19 compatibility, the router offers excellent performance on 4G LTE networks as well, reaching speeds of up to 1.6 Gbps on downloads. The use of 4x4 MIMO technology guarantees a stable connection even in crowded networks.

PoE in/out and IP55 protection

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Powering peripherals has never been easier. The Teltonika OTD500 offers PoE in to power the router via Ethernet cable and PoE out to power other devices such as IP cameras. With an IP55 rating, the router is resistant to harsh weather conditions, making it ideal for outdoor applications .

Remote management and security at the highest level

The router works with Teltonika RMS (Remote Management System), allowing full control from anywhere in the world. With advanced features such as firewall, VPN, and protection against DDoS attacks, your network remains secure and stable. Integrated monitoring tools, such as traffic statistics and signal graphs, give you a complete view of your network's performance.

Versatility and convenience with dual SIM and eSIM

The router supports dual SIM, allowing automatic switching between cards in case of weak signal, roaming or data overage. The built-in eSIM allows management of up to 7 profiles without the need for physical SIM cards. This makes the device ideal for mobile and IoT applications where security and connection availability are key.

- eSIM Supports up to 7 profiles, automatic switching, no data plan included
- Mobile module 5G Sub-6Ghz SA/NSA (DL: 3.4 Gbps, UL: 900 Mbps), LTE Cat 19 (DL: 1.6 Gbps, UL: 200 Mbps), 3G
- Ethernet Ports 2 x Gigabit Ethernet (10/100/1000 Mbps), PoE in/out support
- Dual SIM Automatic switching between SIM cards in case of weak signal or roaming
- WiFi Supports IEEE 802.11 standard, speeds up to 867 Mbps
- Power supply PoE in: 42.5-57 VDC, PoE out: 15 W
- Resistance IP55 class, operating temperature range: -40°C to 55°C
- Management system Teltonika RMS (Remote Management System)
- VPN OpenVPN, WireGuard, IPsec, ZeroTier, DMVPN
- Security features Firewall, DDoS protection, VLAN, digital key authentication

Summary: Teltonika OTD500100000. Networking standards: IEEE 802.1x, IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, Ethernet interface type: Gigabit Ethernet, Cabling technology: 10/100/1000Base-T(X). Mobile network generation: 5G, 4G standard: LTE. Routing protocols: BGP, EIGRP, NHRP, OSPFv2, RIP-1, RIP-2. Security algorithms: AES, CAST, DES, HTTPS, IPsec, SSH, SSL/TLS, TLS. Compliance certificates: CB, EAC, RCM, UKCA, WEEE | Vendor Homepage: <https://teltonika-networks.com/products/routers/otd500> | 3G/4G USB modem compatibility: No | DSL

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

WAN: No | Ethernet WAN: Yes | SFP WAN: No | SIM card slot: Yes | Auto MDI/MDI-X: Yes | Cabling technology: 10/100/1000Base-T(X) | Ethernet interface type: Gigabit Ethernet | Ethernet LAN data rates: 10/100/1000 | Networking standards: IEEE 802.1x/IEEE 802.3/IEEE 802.3af/IEEE 802.3at/IEEE 802.3az/IEEE 802.3u | VLAN support: Yes | 4G standard: LTE | Mobile network generation: 5G | Short Message Service (SMS): Yes | Quality of Service (QoS) support: Yes | Reset button: Yes | Universal Plug and Play (UPnP): Yes | Web-based management: Yes | Ethernet LAN (RJ-45) ports: 2 | Power over Ethernet (PoE) ports quantity: 2 | DHCP client: No | DHCP server: Yes | DMZ support: Yes | Routing protocols: BGP/EIGRP/NHRP/OSPFv2/RIP-1/RIP-2 | DoS attack prevention: Yes | Firewall: Yes | Network address translation (NAT): Yes | Security algorithms: AES/CAST/DES/HTTPS/IPSec/SSH/SSL/TLS/TLS | System event log: Yes | URL filtering: Yes | Compliance certificates: CB/EAC/RCM/UKCA/WEEE | Flash memory: 16 | Internal memory: 256 | Internal memory type: DDR3 | Operating system installed: RutOS | Housing material: Plastic, Polycarbonate (PC) | Product colour: White | Power consumption (max): 9 | Power consumption (typical): 2.5 | Power over Ethernet (PoE): Yes | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 55 | Depth: 235 | Height: 49.3 | Weight: 385 | Width: 110 | Units per Pallet: 0 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.001613 | Unit Calculated Weight: 0.41

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903