



# Power Supply TECNOWARE FAL551FSP12 ATX 550 W FAL551FSP12



Modelis: FAL551FSP12

Gamintojas: TECNOWARE

EAN: 8026475183408

Prekės kodas: 356987

## 28.99€

Internal power supply for personal computer, 550W power, input voltage 230 Vac, 50/60 Hz, conforms to ATX 12V v.2.31 specifications, main switch, surge protection, overload protection, short circuit protection, high MTBF, high reliability, quiet operation, 12 cm silent fan, temperature control of the fan speed, Flat type connection cables from 500mm to 800mm, 1 x 20+4-pin connector, 1 x 12V 4+4-pin connector, 1 x 6+2 PCI-E connector, 2 x Molex connectors, 4 x Sata connector, dimensions 150x140x86 mm, weight 1.0 Kg, black color, CE certification, RoHS. Long Description: Tecnoware Free Silent PRO 550. Total power: 550 W, AC input voltage: 180 - 264 V, AC input frequency: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 50 cm, PCI Express power cable length: 50 cm. Purpose: PC, Power supply unit (PSU) form factor: ATX. Product colour: Black, Fan diameter: 12 cm, Number of fans: 1 fan(s). Compliance certificates: CE, RoHS | Vendor Homepage: <https://www.tecnoware.com/en-US/Dettaglio/Articolo/883>

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

| Bullet Points:

- Internal Power Supply for Computers
- High Efficiency (>85%) and High Operation Noise
- Active PFC >0.9
- Dimensions: 140x86x150 mm (WxHxD)
- Input voltage 230 Vac 50Hz
- Temperature control of the fan speed
- Flat connection cables from 500mm to 800mm
- Surge protection
- Overload protection
- Short circuit protection

| Total power: 550 | 80 PLUS certification: No | Motherboard power connector: 20+4 pin ATX | AC input voltage: 180 - 264 | Motherboard power cable length: 500 | Number of SATA power connectors: 4 | AC input frequency: 47 - 63 | Peripheral (Molex) power connectors (4-pin): 2 | Input current: 5 | Power factor: 0.9 | PCI Express power connectors (6+2 pin): 1 | Power Factor Correction (PFC) type: Active | PCI Express power cable length: 500 | CPU power connector (4+4 pin): Yes | CPU power cable length: 550 | Combined power (+3.3V): 170 | Combined power (+12V): 360 | Combined power (+5V): 170 | Combined power (-12V): 9.6 | Combined power (+5Vsb): 12.5 | Max output current (+3.3V): 23 | Max output current (+12V): 30 | Purpose: PC | Power supply unit (PSU) form factor: ATX | Max output current (+5V): 24 | Max output current (-12V): 0.8 | Product colour: Black | Max output current (+5Vsb): 2.5 | ATX version: 2.31 | ATX power connector (20+4 pin): Yes | Fan diameter: 120 | Number of fans: 1 | Operating temperature (T-T): 0 - 40 | Storage temperature (T-T): -15 - 40 | Width: 140 | Depth: 150 | Height: 86 | Weight: 1000 | Compliance certificates: CE/RoHS | On/off switch: Yes | Efficiency: 85 | Cabling type: Non-Modular | Package type: Box | Power protection features: Overload/Short circuit/Surge protection | Model name: FAL551FSP12 | Units per Pallet: 0 | Units per Shipping Box: 8 | Unit Calculated Volume: 0.0034 | Unit Calculated Weight: 1.13