SHOPRO

Power Supply ADATA XPG PYLON II ATX 3.1 750 Watts Efficiency 80 PLUS BRONZE MTBF 100000 hours PYLON750IIB-BKCEU

Modelis: PYLON750IIB-BKCEU

Gamintojas: ADATA

EAN: 4711658150875

Prekės kodas: 357251

67.99€

PYLON II

UNLEASH THE SURGE

The PYLON II Bronze PSU delivers 80 PLUS Bronze efficiency, cutting energy costs without sacrificing performance. Designed to meet Intel ATX 3.1 standards, it offers a future-ready solution for high-

demand components. Equipped with a quiet and durable FDB fan, it ensures efficient cooling for a stable and noise-free experience. Backed by 8 industrial-grade protections and a 5-year warranty, the PYLON II guarantees long-term reliability and peace of mind for your build.

Intel ATX 3.1 Compliant, Future-Ready Design

Designed with the latest Intel ATX 3.1 standards, the PYLON II is equipped with 12V-2x6 connector*, ensuring compatibility with high-performance components. It's engineered to meet the evolving needs of modern systems.

Quiet, Efficient Cooling with FDB Fan

Equipped with a 135mm FDB fan, the PYLON II ensures quiet operation and long-lasting durability. It keeps your system cool even under demanding workloads, delivering optimal cooling without compromising on noise levels.

Comprehensive Protection for Peace of Mind

With 8 industrial-grade protections, the PYLON II shields your system from power surges, short circuits, and other potential risks. This protection, combined with a 5-year warranty, offers long-term peace of mind.

Summary: XPG PYLON II 750w BROZNZE Power Supply. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 24-pin ATX. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 13.5 cm. Width: 150 mm, Depth: 150 mm, Height: 86 mm | Vendor Homepage: https://www.xpg.com/us/xpg/pc-components-pylonll | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Input current: 10 | Max output current (+12V): 62.5 | Max output current (+3.3V): 22 | Max output current (+5V): 22 | Max output current (+5Vsb): 3 | Max output current (-12V): 0.3 | Power factor: 0.99 | Power Factor Correction (PFC) type: Active | Power protection features: No load operation/Over current/Over power/Over voltage/Overheating/Short circuit/Surge & inrush/Under voltage | Total power: 750 | EPS power connector (8-pin): Yes | Motherboard power connector: 24-pin ATX | Number of SATA power connectors: 6 | PCI Express power connectors (6+2 pin): 1 | Peripheral (Molex) power connectors (4-pin): 2 | 80 PLUS certification: 80 PLUS Bronze | ATX version: 3.1 | Bearing technology: FDB | Mean time between failures (MTBF): 100000 | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 135 | Fan speed: 0 - 2300 | Number of fans: 1 | On/off switch: Yes | Product

colour: Black | Depth: 150 | Height: 86 | Weight: 1800 | Width: 150 | Model name: XPG PYLON II | Units per Shipping Box: 1 | Unit Calculated Volume: 0.009555 | Unit Calculated Weight: 2.42