



## CABLE DP TO DP 2M/CAC-1094 CLUB3D



Modelis: CAC-1094

Gamintojas: CLUB3D

EAN: 8719214473549

Prekės kodas: 357546

# 36.99€

The Club 3D CAC-1094 DisplayPort™ 2.1 Cable enables the connection of your DisplayPort™ supported (Gaming) PC or Laptop to an (Ultra) High Resolution Monitor or other DisplayPort™ supported device. DisplayPort™ 2.1 UHBR10/13.5/20 up till 80 Gbps, also has support for Display Stream Compression 1.2 (DSC), Forward Error Correction, and extends the maximum number of inline audio channels to 32. Thanks to improvements in both the DisplayPort™ connector and cable design, the new VESA certified DP80 UHBR cables enable consumers to get the highest performance possible from their VESA certified devices. These new cables are backed by VESA's UHBR Certification Program, which provides added assurance that if your cable has the DP40 or DP80 logo from VESA, it will meet the specs for the highest data rates supported by current and future products certified by VESA.

- **EXCEPTIONAL CABLE LENGTH:** This is the first DP80 cable to reach two metres.
- **HIGH PERFORMANCE:** The DP80 is the top-tier version of the DisplayPort™ 2.1 standard. It can

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

support a video signal of up to 8K60Hz with HDR without compression. With DSC enabled, the frequency can be increased to 8K240Hz.

- VESA CERTIFIED: This ensures that the highest standards are met in terms of both physical and electrical quality in a 26 AWG cable.
- QUALITY CONSTRUCTION: Nickel-plated connectors with PVC strain reliefs for durability; Twisted Pair wire with braided alloy shield for enhanced EMI protection.

- • EXCEPTIONAL CABLE LENGTH: This is the first DP80 cable to reach two metres.
- • HIGH PERFORMANCE: The DP80 is the top-tier version of the DisplayPort™ 2.1 standard. It can support a video signal of up to 8K60Hz with HDR without compression. With DSC enabled, the frequency can be increased to 8K240Hz.
- • VESA CERTIFIED: This ensures that the highest standards are met in terms of both physical and electrical quality in a 26 AWG cable.
- • QUALITY CONSTRUCTION: Nickel-plated connectors with PVC strain reliefs for durability; Twisted Pair wire with braided alloy shield for enhanced EMI protection.

Summary: CLUB3D DisplayPort™ 2.1 VESA DP80 Certified Cable 8K240Hz 2m/6.56ft. Cable length: 2 m, Connector 1: DisplayPort, Connector 2: DisplayPort. Weight: 150 g. Package width: 175 mm, Package depth: 175 mm, Package height: 45 mm. Harmonized System (HS) code: 8544 4290 | Vendor Homepage: [https://www.club-3d.com/en/detail/2699/displayportt\\_2.1\\_vesa\\_dp80\\_certified\\_cable\\_8k240hz\\_2m-6.56ft/](https://www.club-3d.com/en/detail/2699/displayportt_2.1_vesa_dp80_certified_cable_8k240hz_2m-6.56ft/) | AWG wire size: 26 | Cable length: 2 | Cable type: Round cable | Connector 1: DisplayPort | Connector 1 form factor: Straight | Connector 1 gender: Male | Connector 2: DisplayPort | Connector 2 form factor: Straight | Connector 2 gender: Male | Connector contacts plating: Nickel | Connector material: Gold | Data transfer rate: 80 | Display Stream Compression (DSC): Yes | DisplayPort version: 2.1 | Magnetically shielded: Yes | Maximum refresh rate: 240 | Maximum resolution: 10240 x 4320 | Plug and Play: Yes | Product colour: Black | Supported graphics resolutions: 10328 x 7760/7680 x 4320 | Supported video modes: 4320p | Weight: 150 | Package depth: 175 | Package height: 45 | Package weight: 216 | Package width: 175 | Paper/cardboard packaging weight: 63 | Plastic packaging weight: 3 | Total paper/cardboard packaging weight: 630 | Total plastic packaging weight: 30 | Harmonized System (HS) code: 8544 4290 | Model name: CAC-1094 | Units per Pallet: 0 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.001693 | Unit Calculated Weight: 0.21

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903