



**Switch DAHUA
DH-CS4010-
8ET2GT-110
Switch layer L2
8xRJ-45 ports RJ-
45 Ports Type
Fast Ethernet
(10/100)
2xGigabit
Ethernet
(copper) ports
quantity
8xPower over
Ethernet (PoE)
ports quantity
Total Power
over Ethernet
(PoE) budget
110 W CS4010-
8ET2GT-110**

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Modelis: CS4010-8ET2GT-110

Gamintojas: DAHUA

Prekės kodas: 357634

70.99€

DH-CS4010-8ET2GT-110 | Switch layer L2 | 8xBasic switching RJ-45 Ethernet ports quantity | Basic switching RJ-45 Ethernet ports type Fast Ethernet (10/100) | Switching capacity 5.6 Gbit/s | Forwarding rate 4.17 Mpps | Power source DC/PoE | 8xPower over Ethernet (PoE) ports quantity | Total Power over Ethernet (PoE) budget 110 W | Width 184.6 mm | Depth 103.3 mm | Height 27 mm
Long Description: Dahua Technology CS4010-8ET2GT-110. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 10. MAC address table: 8000 entries, Switching capacity: 5.6 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE.... DC input voltage: 54 V. Power connector: DC-in jack. Power over Ethernet (PoE). Wall mountable | Vendor Homepage:

<https://transmission.dahuasecurity.com/en/product->

[list/business/cloudmanagementsolution/networkswitch/cs4010-8et2gt-110](https://transmission.dahuasecurity.com/en/product-list/business/cloudmanagementsolution/networkswitch/cs4010-8et2gt-110) | Bullet Points:

- 8 × RJ-45 10/100 Mbps PoE ports, 2 × RJ-45 Gigabit ports
- 110 W total PoE budget, 802.3af/at on all PoE ports, additional 802.3 bt on red ports
- DIP switch to fast turn on/off working mode of Cloud-Managed, PoE Watchdog, Long Distance PoE
- Wide operating temperature ranging from -10 °C to 55 °C
- Supports VLAN and loop protection
- WEB-managed and centralized cloud management through the DoLink App and performs real-time monitoring of the network
- Easy config to auto detect and set up network and security systems

| Rack mounting: No | Networking standards: IEEE 802.1Q/IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3az/IEEE 802.3bt/IEEE 802.3u/IEEE 802.3x | 10G support: No | Model name:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

CS4010-8ET2GT-110 | Power source: DC/PoE | Power supply included: Yes | Switch type: Managed | DC input voltage: 54 | Input current: 2.22 | Switch layer: L2 | Compliance certificates: CE | Multicast support: Yes | Basic switching RJ-45 Ethernet ports quantity: 10 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power over Ethernet (PoE): Yes | Fast Ethernet (copper) ports quantity: 8 | Gigabit Ethernet (copper) ports quantity: 2 | Product colour: Blue | Switching capacity: 5.6 | Housing material: Metal | Forwarding rate: 4.17 | MAC address table: 8000 | Reset button: Yes | LED indicators: Yes | DHCP features: DHCP client | Cables included: AC | Power over Ethernet (PoE) ports quantity: 8 | Width: 103.3 | Operating temperature (T-T): -10 - 55 | Storage temperature (T-T): -40 - 70 | Operating relative humidity (H-H): 10 - 90 | Storage relative humidity (H-H): 5 - 95 | Depth: 184.6 | Height: 27 | Jumbo frames support: Yes | Jumbo frames: 9216 | Port mirroring: Yes | Cloud-managed: Yes | Web-based management: Yes | Manual: Yes | Weight: 360 | Total Power over Ethernet (PoE) budget: 110 | Wall mountable: Yes | IP-MAC-Port binding: Yes | Loop protection: Yes | Broadcast storm control: Yes | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | Packet buffer memory: 4 | VLAN support: Yes | Number of VLANs: 32 | Package width: 137 | Package depth: 252 | Package height: 113 | Package weight: 1090 | Mean time between failures (MTBF): 3359638 | Power connector: DC-in jack | Units per Pallet: 0 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.003713 | Unit Calculated Weight: 1.13

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903