

Switch DAHUA DH-SG4010-2F SG4010-2F



Modelis: SG4010-2F

Gamintojas: DAHUA

EAN: 6923172597670

Prekės kodas: 357636

80.99€

Equipped with a high performance switching engine, the 8 Port All- Gigabit Managed Switch performs optimally. It has low transmission delay, large buffer and is highly reliable. It also has a strong switching

capability and optimizes transmission performance when accessing Ultra HD videos. With its full metal design and fanless design, the device has great heat dissipation and is low power consumption, working

in environments ranging from -10°C to 55°C ($+14^{\circ}\text{F}$ to $+131^{\circ}\text{F}$). With protection against overvoltage, EMC and overcurrent from power input terminals, the switch effectively resists interference from static electricity, lightning, and pulses. It also offers a variety of services, supporting IGMP Snooping, Link Aggregation, QoS, LLDP, STP/RSTP and various web and network management software based on SNMP.

Link Layer Discovery Protocol (LLDP)

Enables network devices to advertise their information mutually, allowing you to conveniently

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

monitor and manage devices in the local topology. This makes it easy for administrators to effectively perform troubleshooting.

Quality of Service (QoS)

Uses mechanisms designed to control bandwidth, delay, jitter, and loss to ensure the performance of services when the capacity is limited.

Spanning Tree Protocol (STP)

Uses algorithms that calculate the best loop-free path through a Layer 2 network while providing path redundancy to prevent the occurrence of broadcast storms and enhance the stability of operations and services.

Link Aggregation

Combines multiple physical links into one virtual channel for dynamic redundancy and load balancing, ensuring that the connection remains stable.

IGMP Snooping

Listens to multicast traffic, and solely forwards information to registered clients based on the multicast forwarding table. This ensures the safety of information and improves network efficiency.

Fanless Design

The fanless design reduces noise, enhances user experience, reduces mechanical losses and improves service life to a certain extent.

- Layer 2 network managed switch
- Network redundancy: STP/RSTP
- Static link aggregation and LACP
- Devices discovery based on LLDP
- QoS (IEEE802.1p/1Q) to increase determinism
- IGMP Snooping
- Fanless design
- EMC high protection design

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Desktop and wall-mounted installation

Summary: Dahua Technology SG4010-2F. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8, Console port: RJ-45. Full duplex. MAC address table: 8000 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3u, IEEE.... DC input voltage: 12 V. Wall mountable | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Transmission/IT-Channel-Products/Managed-Switch/SG4010-2F> | Cloud-managed: No | Quality of Service (QoS) support: Yes | Switch layer: L2 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Console port: RJ-45 | Gigabit Ethernet (copper) ports quantity: 8 | SFP module slots quantity: 2 | Uplink ports quantity: 2 | 10G support: No | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | Full duplex: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1p/IEEE 802.1Q/IEEE 802.1x/IEEE 802.3/IEEE 802.3ab/IEEE 802.3ad/IEEE 802.3u/IEEE 802.3x/IEEE 802.3z | Number of VLANs: 4000 | Spanning tree protocol: Yes | Virtual LAN features: Port-based VLAN/Tagged VLAN | VLAN support: Yes | Fiber ethernet cabling technology: 1000BASE-X | Forwarding rate: 14.88 | Jumbo frames: 9000 | Jumbo frames support: Yes | MAC address table: 8000 | Packet buffer memory: 4.1 | Switching capacity: 20 | Access Control List (ACL): Yes | DHCP features: DHCP client | IGMP snooping: Yes | Multicast support: Yes | Management protocols: SNMP V1/V2C/V3 | Housing material: Steel | LED indicators: Yes | Product colour: Black | Rack mounting: No | Reset button: Yes | Wall mountable: Yes | Fanless: Yes | Mean time between failures (MTBF): 2322286.99 | DC input voltage: 12 | Input current: 1 | Power consumption (max): 12 | Power source: DC | Power over Ethernet (PoE): No | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -10 - 55 | Depth: 240 | Height: 28 | Weight: 640 | Width: 104 | Package depth: 316 | Package height: 82 | Package weight: 1040 | Package width: 240 | Sustainability compliance: Yes | Compliance certificates: CE | Model name: DH-SG4010-2F | Units per Pallet: 0 | Units per Shipping Box: 12 | Unit Calculated Volume: 0.007659 | Unit Calculated Weight: 1.18

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903