



Mainboard
ASROCK Intel
H610 LGA1700
Micro-ATX
Memory DDR4
Memory slots 2
1xPCI-Express
3.0 1x 1xPCI-
Express 4.0 16x
1xM.2 1x15pin
D-sub 1xHDMI
1xAudio-In
1xAudio-Out
1xMicrophone
4xUSB 2.0
2xUSB 3.2
1xPS/2 1xRJ45
H610M-
HVS/M.2R2.0

Modelis: H610M-HVS/M.2R2.0

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Gamintojas: ASROCK

EAN: 4710483939914

Prekės kodas: 358142

65.99€

Digi Power

Unlike traditional motherboards that use analog power, this motherboard uses a next generation digital PWM (Pulse-Width Modulation) design, which provides CPU Vcore voltage more efficiently and smoothly, so that the stability and lifespan of the motherboard is greatly enhanced.

Ultra M.2 32Gb/s (PCIe Gen3 x4 & SATA3)

The PCIe Gen3 x4 Ultra M.2 interface pushes data transfer speeds up to 32Gb/s. In addition, it also supports SATA3 6Gb/s M.2 modules.

Premium Power Choke

Compared to traditional chokes, ASRock's premium power chokes effectively make the saturation current up to three times better, thus providing enhanced and improved Vcore voltage to the motherboard.

Sapphire Black PCB

Pure black PCB appearance. The new Sapphire Black PCB represents rock-solid quality and gives the motherboard a more mysterious touch.

Full Spike Protection

Some sensitive digital components on the motherboard are vulnerable to power surges, the excessive current may cause your system to malfunction immediately. ASRock Full Spike Protection includes various technologies to prevent your motherboard's components from being damaged by

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

these unexpected voltage spikes.

- Supports 13th Gen & 12th Gen Intel® Core™ Processors (LGA1700)
- 7 Phase Power Design
- Supports DDR4 3200MHz
- 1 PCIe 4.0 x16, 1 PCIe 3.0 x1
- Graphics Output Options: HDMI, D-Sub
- Realtek ALC897 7.1 CH HD Audio Codec
- 4 SATA3
- 1 Ultra M.2 (PCIe Gen3 x4)
- 4 USB 3.2 Gen1 (2 Rear, 2 Front)
- 6 USB 2.0 (4 Rear, 2 Front)
- Realtek Gigabit LAN

Summary: Asrock H610M-HVS/M.2 R2.0. Processor manufacturer: Intel, Processor socket: LGA 1700, Compatible processor series: Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7. Supported memory types: DDR4-SDRAM, Maximum internal memory: 64 GB, Memory slots type: DIMM. Supported storage drive interfaces: M.2, SATA III, Supported storage drive types: HDD & SSD. Maximum resolution: 4096 x 2160 pixels. Ethernet interface type: Gigabit Ethernet, LAN controller: Realtek RTL8111H | Vendor Homepage: <https://www.asrock.com/MB/Intel/H610M-HVSM.2%20R2.0/index.asp#Specification> | Audio chip: Realtek ALC897 | Audio output channels: 7.1 | Certification: - FCC, CE - ErP/EuP ready (ErP/EuP ready power supply is required) | Component for: PC | Motherboard chipset: Intel H610 | Motherboard chipset family: Intel | Motherboard form factor: micro ATX | PC health monitoring: CPU/Fan/Voltage/Water cooling | Windows operating systems supported: Windows 10 Education x64/Windows 11 x64 | Compatible processor series: Intel® Core™ i3/Intel® Core™ i5/Intel® Core™ i7 | Maximum number of SMP processors: 1 | Processor manufacturer: Intel | Processor socket: LGA 1700 | ECC compatibility: Non-ECC | Maximum internal memory: 64 | Memory channels: Dual-channel | Memory slots type: DIMM | Number of memory slots: 2 | Supported memory clock speeds: 3200 | Supported memory types: DDR4-SDRAM | Unbuffered memory: Yes | Supported storage drive interfaces: M.2,SATA III | Supported storage drive types: HDD & SSD | HDCP: Yes | Maximum resolution: 4096 x 2160 | Parallel processing technology support: Not supported | ATX Power connector (24-pin): Yes | Chassis intrusion connector: Yes | CPU fan connector: Yes | EPS power connector (8-pin): Yes | Front panel connector: Yes | TPM connector: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

USB 2.0 connectors: 2 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 2 | Ethernet LAN (RJ-45) ports: 1 | HDMI ports quantity: 1 | Headphone outputs: 1 | Line-in: Yes | Microphone in: Yes | PS/2 ports quantity: 1 | USB 2.0 ports quantity: 4 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | VGA (D-Sub) ports quantity: 1 | Ethernet interface type: Gigabit Ethernet | Ethernet LAN: Yes | LAN controller: Realtek RTL8111H | Wake-on-LAN ready: Yes | Wi-Fi: No | Number of M.2 (M) slots: 1 | PCI Express x1 (Gen 3.x) slots: 1 | PCI Express x16 (Gen 4.x) slots: 1 | BIOS memory size: 128 | BIOS type: UEFI AMI | System Management BIOS (SMBIOS) version: 2.7 | Depth: 188 | Width: 223 | Cables included: SATA | Model: H610M-HVS/M.2 R2.0 | Units per Pallet: 0 | Units per Shipping Box: 20 | Unit Calculated Volume: 0.004511 | Unit Calculated Weight: 0.876

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903