



IP security camera DAHUA Technology IPC- HDW1439V-A-IL White



Modelis: 43164

Gamintojas: DAHUA

EAN: 6923172570352

Prekės kodas: 361314

68.99€

Certification: CE-LVD: EN62368-1 CE-EMC:: Electromagnetic Compatibility Directive 2014/30/EU
2023-07-21 | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings:
Ensure that the product is properly installed and protected against falling. | Warnings: The product
contains electronic components do not dispose of with the normal household waste. | Power source
type: DC, PoE | Built-in microphone: Yes | Supported graphics resolutions: 704 x 480 | Supported
graphics resolutions: 2560 x 1440 | Supported graphics resolutions: 704 x 576 | Supported graphics
resolutions: 1280 x 960 | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics
resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 352 x 288 | Supported graphics
resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 352 x 240 | Supported
graphics resolutions: 2304 x 1296 | Tilt angle range: 0 - 78° | Maximum resolution: 2560 x 1440
pixels | Product colour: White | Connectivity technology: Wired | Weight: 330 g | Detect distance: 64
m | Noise reduction technology: 3D noise reduction | Placement supported: Indoor & outdoor | Lens

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be
išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš
išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

viewing angle, vertical: 52° | Frame rate: 30 fps | Sensor type: HD CMOS | Recognize distance: 12.8 m | Mounting type: Ceiling/wall | Optical sensor size: 25.4 / 2.9 mm (1 / 2.9") | Lens viewing angle, horizontal: 94° | Region of Interest (ROI) encoding: Yes | Gain control type: Auto | Camera shutter speed: 1/3 - 1/100000 s | Bit rate control: Constant Bit Rate (CBR), Variable Bit Rate (VBR) | Lens viewing angle, diagonal: 111° | Supported video modes: 720p | Observe distance: 25.6 m | Power consumption (max): 4.6 W | Smart IR: Yes | Video streaming: Yes | Width: 109.9 mm | Web browser: Yes | Operating temperature (T-T): -40 - 60 °C | Number of cameras: 1 | Power consumption (typical): 2 W | Video compression formats: H.264H | Depth: 109.9 mm | Focal length range: 2.8 mm | Supported video modes: 1080p | Closest focusing distance: 1.1 m | Bit rate: H.264: 32 - 4096Kbps H.265: 12 - 4096Kbps | Video compression formats: H.264+ | Progressive scan: Yes | Streaming method: Multicast | Wi-Fi: No | Maximum aperture number: 1.6 | Video motion detection: Yes | Form factor: Dome | Identify distance: 6.4 m | Signal-to-Noise Ratio (SNR): 56 dB | Noise reduction: Yes | Audio codecs: G.711a, G.711Mu, G.726, PCM | Type: IP security camera | Ethernet LAN: Yes | Night vision: Yes | Mirror: Yes | Management software: Smart PSS, Smart PSS Lite, DSS, DMSS, P2P | International Protection (IP) code: IP67 | Ethernet LAN (RJ-45) ports: 1 | Power consumption (Power over Ethernet (PoE)): 2.9 W | Video compression formats: H.265+ | Smartphone/tablet remote support: Yes | Video compression formats: H.265 | Height: 100.9 mm | DC output voltage: 12 | Mobile operating systems supported: iOS | ROM capacity: 128 MB | Video compression formats: H.264 | Mobile operating systems supported: Android | Wide Dynamic Range (WDR): 120 dB | White balance: Auto | Night vision distance: 30 m | Power over Ethernet (PoE) voltage range: 48 V | Pan range: 0 - 360° | Day/night mode: Yes | White balance: Outdoor | Internal memory: 128 MB | White balance: Manual | White balance: Street lamp | Number of illumination LEDs: 1 / 1 | Active tampering alarm: Yes | Total megapixels: 4 MP | Storage temperature (T-T): -30 - 70 °C | Supported network protocols: IPv4 IPv6 HTTP TCP UDP ARP RTP RTSP SMTP FTP DHCP DNS DDNS NTP Multicast | White balance: Natural | Video compression formats: H.264B | Camera shutter type: Mechanical | Digital Wide Dynamic Range (DWDR): Yes | Camera shutter type: Electronic | Number of lenses: 1 | Number of effective pixels (H x V): 2560 x 1440 pixels | Number of sensors: 1 | Ethernet interface type: Fast Ethernet | Back Light Compensation (BLC): Yes | LED type: IR / White light LED | Operating relative humidity (H-H): 0 - 95%

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903