



IP security camera DAHUA Technology IPC- HFW1439TL1-A- IL White



Modelis: IPC-HFW1439TL1-A-IL

Gamintojas: DAHUA

EAN: 6923172570796

Prekės kodas: 361315

70.99€

Certification: CE-LVD: EN62368-1 CE-EMC:: Electromagnetic Compatibility Directive 2014/30/EU
2023-07-21 | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings:
Ensure that the product is properly installed and protected against falling. | Warnings: The product
contains electronic components do not dispose of with the normal household waste. | Audio codecs:
G.711a, G.711Mu, G.726, PCM | Video compression formats: H.264 | Detect distance: 64 m |
Streaming method: Multicast | Closest focusing distance: 1.1 m | Lens viewing angle, diagonal: 111°
| Video streaming: Yes | Video compression formats: H.264+ | Gain control type: Auto | DC output
voltage: 12 | Mounting type: Ceiling/wall | Smart IR: Yes | Recognize distance: 12.8 m | Mobile
operating systems supported: iOS | Web browser: Yes | ROM capacity: 128 MB | Mobile operating
systems supported: Android | Region of Interest (ROI) encoding: Yes | Video compression formats:
H.264H | Maximum aperture number: 1.6 | Day/night mode: Yes | Video compression formats:
H.264B | Video compression formats: H.265+ | Video compression formats: H.265 | Lens viewing

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

angle, vertical: 52° | Lens viewing angle, horizontal: 94° | Observe distance: 25.6 m | Noise reduction technology: 3D noise reduction | Sensor type: HD CMOS | Placement supported: Indoor & outdoor | Identify distance: 6.4 m | Video motion detection: Yes | Night vision: Yes | Power consumption (Power over Ethernet (PoE)): 2.9 W | Number of lenses: 1 | Smartphone/tablet remote support: Yes | Management software: Smart PSS, Smart PSS Lite, DSS, DMSS, P2P | Power over Ethernet (PoE) voltage range: 48 V | Number of sensors: 1 | Mirror: Yes | Active tampering alarm: Yes | Number of effective pixels (H x V): 2560 x 1440 pixels | International Protection (IP) code: IP67 | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | Bit rate control: Constant Bit Rate (CBR), Variable Bit Rate (VBR) | Camera shutter type: Electronic | Optical sensor size: 25.4 / 2.9 mm (1 / 2.9") | Number of illumination LEDs: 2 / 2 | Camera shutter type: Mechanical | Form factor: Bullet | White balance: Manual | Frame rate: 30 fps | Power consumption (typical): 2 W | Supported video modes: 720p | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | White balance: Street lamp | Bit rate: H.264: 32 - 4096Kbps H.265: 12 - 4096Kbps | Product colour: White | White balance: Auto | Number of cameras: 1 | Width: 80.2 mm | Signal-to-Noise Ratio (SNR): 56 dB | Camera shutter speed: 1/3 - 1/100000 s | Supported graphics resolutions: 2560 x 1440 | White balance: Outdoor | Power source type: DC, PoE | Supported graphics resolutions: 352 x 288 | Supported video modes: 1080p | Progressive scan: Yes | Maximum resolution: 2560 x 1440 pixels | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 640 x 480 (VGA) | Digital Wide Dynamic Range (DWDR): Yes | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Wi-Fi: No | Type: IP security camera | White balance: Natural | Supported graphics resolutions: 1280 x 720 (HD 720) | Night vision distance: 30 m | Operating temperature (T-T): -40 - 60 °C | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Wide Dynamic Range (WDR): 120 dB | Storage temperature (T-T): -30 - 70 °C | Height: 76.2 mm | Focal length range: 2.8 mm | Built-in microphone: Yes | Total megapixels: 4 MP | Pan range: 0 - 360° | Weight: 310 g | Power consumption (max): 6.4 W | Ethernet interface type: Fast Ethernet | Connectivity technology: Wired | Operating relative humidity (H-H): 0 - 95% | Internal memory: 128 MB | Noise reduction: Yes | LED type: IR / White light LED | Tilt angle range: 0 - 90° | Supported network protocols: IPv4 IPv6 HTTP TCP UDP ARP RTP RTSP SMTP FTP DHCP DNS DDNS NTP Multicast | Depth: 197.9 mm | Ethernet LAN: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903