IP CAMERA DAHUA IPC-HDW2849TM-S-IL-0280B

Modelis: IPC-HDW2849TM-S-IL-0280B

Gamintojas: DAHUA

EAN: 6923172581549

Prekės kodas: 361323

134.99€

Certification: LVD: EN62368-1 EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B 2023-04-10 | Supported graphics resolutions: 704 x 576 | Frame rate: 30 fps | Supported graphics resolutions: 1280 x 720 (HD 720) | Video compression formats: H.264H | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Number of sensors: 1 | Progressive scan: Yes | Maximum resolution: 3840 x 2160 pixels | Video compression formats: H.264+ | Supported graphics resolutions: 640 x 480 (VGA) | Type: IP security camera | White balance: Natural | White balance: Auto | Diameter: 12.2 cm | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Video compression formats: H.265+ | White balance: Street lamp | Housing material: Metal, Plastic | Supported graphics resolutions: 352 x 240 | Number of cameras: 1 | Supported graphics resolutions: 352 x 288 | Video compression formats: M-JPEG | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Web browser: Yes | Video compression formats: H.264B | Wi-Fi: No | International Protection (IP) code: IP67 | Ethernet interface type: Fast Ethernet | Operating relative humidity (H-H): 0 - 95% | Gain control type: Auto/Manual | White balance: Manual | White balance: Outdoor | Closest focusing distance: 1.5 m | Total megapixels: 8 MP

| Camera shutter speed: 1/3 - 1/100000 s | Region of Interest (ROI) encoding: Yes | Bluetooth: No | Video compression formats: H.264 | Bit rate: H.264: 32 kbps–8192 kbps H.265: 12 kbps–8192 kbps | Power consumption (Power over Ethernet (PoE)): 5.9 W | Lens type: Fixed focal length lens | Signal-to-Noise Ratio (SNR): 56 dB | Number of lenses: 1 | Quality of Service (QoS) support: Yes | Mobile operating systems supported: iOS | Internal memory: 256 MB | Mounting type: Ceiling | Highlight Compensation (HLC): Yes | ROM capacity: 128 MB | Web-based management: Yes | Night vision distance: 30 m | Mobile operating systems supported: Android | Wide Dynamic Range (WDR): 120 dB | Product colour: White | Storage temperature (T-T): -40 - 60 °C | Maximum aperture number: 1.6 | Video compression formats: H.265 | Height: 99.1 mm | Adjustment shutter speed: Auto/Manual | Form factor: Dome | Video streaming: Yes | Supported graphics resolutions: 3840 x 2160 | Weight: 480 g | Noise reduction technology: 3D noise reduction | Placement supported: External / Internal | Power source type: DC, PoE | Number of illumination LEDs: 2 | Noise reduction: Yes | DC output voltage: 12 | Operating temperature (T-T): -40 - 55 °C | Back Light Compensation (BLC): Yes | Minimum illumination: 0.008 lx | Power consumption (max): 5 W | Supported graphics resolutions: 2304 x 1296 | Connectivity technology: Wired | Supported graphics resolutions: 1280 x 960 | LED type: IR / White light LED | Supported graphics resolutions: 3072 x 2048 | Networking standards: IEEE 802.3af | Mirror function: Yes | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 2880 x 1620 | Supported graphics resolutions: 2048 x 1536 (QXGA) | Supported graphics resolutions: 3072 x 1728 | Built-in HDD: No | Focal length range: 2.8 mm | Number of users: 20 user(s) | Built-in microphone: Yes | Night vision: Yes | Audio formats supported: PCM | Tilt angle range: 0 - 78° | Audio formats supported: G.711a | Audio formats supported: G.726 | Sensor type: CMOS | Pan range: 0 - 360° | Warnings: The product contains electronic components do not dispose of with the normal household waste. | Lens viewing angle, vertical: 58° | Lens viewing angle, horizontal: 111° | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Lens viewing angle, diagonal: 132° | Audio formats supported: G.711Mu