



Hikvision Digital Technology DS- 2CD1321-I IP Security Camera Outdoor Turret 1920 x 1080 px Ceiling Wall



Modelis: DS-2CD1321-I(2.8mm)(F)

Gamintojas: HIKVISION

EAN: 6941264097921

Prekės kodas: 361353

64.99€

Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Ethernet LAN: Yes | Angle of rotation: 360° | Height: 85.3 mm | Quality of Service (QoS) support: Yes | Package depth: 150 mm | Power consumption (Power over Ethernet (PoE)): 6.5 W | Digital Wide Dynamic Range (DWDR): Yes | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Infra-red wavelength: 850 nm | Form factor: Turret | Image quality adjustment: Brightness | Camera shutter speed: 1/3 - 1/100000 s | Image quality adjustment: Sharpness | Operating temperature (T-T): -30 - 60 °C | Image quality adjustment: Contrast | Sensor type: CMOS | Tilt angle range: 0 - 75° | IP address filtering: Yes | Camera tilt control: Yes | Supported graphics resolutions: 640 x 480 (VGA) | Networking standards: IEEE 802.1x | DC output current: 0.4 A | Built-in HDD: No | Housing material:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Plastic | LED type: IR | Infrared (IR) cut-off filter: Yes | Progressive scan: Yes | Supported graphics resolutions: 320 x 240 | Supported graphics resolutions: 640 x 360 | Video streaming: Yes | Storage relative humidity (H-H): 0 - 95% | Housing material: Metal | Image quality adjustment: Saturation | Web-based management: Yes | Package weight: 556 g | Night vision distance: 30 m | Power consumption (max): 5 W | Wide Dynamic Range (WDR): Yes | HTTPS encryption: Yes | Storage temperature (T-T): -30 - 60 °C | Maximum resolution: 1920 x 1080 pixels | Package width: 150 mm | Camera pan control: Yes | Operating relative humidity (H-H): 0 - 95% | Weight: 320 g | Supported graphics resolutions: 1280 x 960 | Region of Interest (ROI) encoding: Yes | Languages support: English | Digital watermark: Yes | DC output voltage: 12 | Ethernet interface type: Fast Ethernet | Connectivity technology: Wired | Frame rate: 30 fps | Fixed focal length: 2.8 mm | Pan range: 0 - 360° | Languages support: Ukrainian | Product colour: White | Number of users: 32 user(s) | Heartbeat: Yes | Video motion detection: Yes | Privacy masking: Yes | Wi-Fi: No | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | Total megapixels: 2 MP | Gain control type: Auto | Placement supported: Outdoor | Power source type: DC, PoE | Mirror: Yes | Video compression formats: M-JPEG | Type: IP security camera | Number of cameras: 1 | Viewing angle, vertical: 60° | Diameter: 11 cm | Maximum aperture number: 2 | Noise reduction: Yes | Number of sensors: 1 | Video compression formats: H.264+ | Day/night mode: Yes | Bit rate: 32 Kbps - 8 Mbps | Bluetooth: No | Video compression formats: H.264 | Networking standards: IEEE 802.3af | Video compression formats: H.265 | International Protection (IP) code: IP67 | Video compression formats: H.265+ | Mounting type: Ceiling/wall | Anti-flicker: Yes | Noise reduction technology: 3D noise reduction | Night vision: Yes | Number of languages: 2 | Password protection: Yes | Package height: 141 mm | Number of lenses: 1

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903