



Hikvision Digital Technology DS- 2CD2027G2- L(2.8MM) IP Security Camera Outdoor Bullet 1920 x 1080 px Wall

Modelis: DS-2CD2027G2-L(2.8mm)

Gamintojas: HIKVISION

EAN: 6941264057659

Prekės kodas: 361354

72.00€

Certification: Class BFCC SDoC (47 CFR Part 15, Subpart B) CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014) RCM (AS/NZS CISPR 32: 2015) IC VoC (ICES-003: Issue 6, 2016) KC (KN 32: 2015, KN 35: 2015)UL (UL 60950-1) CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013, IEC 62368-1:2014) CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013, IEC 62368-1:2014) BIS (IS 13252(Part 1):2010+A1:2013+A2:2015) LOA (IEC/EN 60950-1)CE-RoHS (2011/65/EU) WEEE (2012/19/EU) Reach (Regulation (EC) No 1907/2006)Reach Regulation (EC) No 1907/2006 | Warnings: The product contains electronic components do not dispose of with the

normal household waste. | Warnings: Avoid direct contact with water to prevent electrical damage. |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Warnings: Ensure that the product is properly installed and protected against falling. | Wide Dynamic Range (WDR): Yes | Connectivity technology: Wired | Form factor: Bullet | Bluetooth: No | Wi-Fi: No | Product colour: White | Highlight Compensation (HLC): Yes | Tilt angle range: 0 - 90° | Viewing angle, horizontal: 107° | Supported video modes: 720p | Maximum resolution: 1920 x 1080 pixels | Supported video modes: 480p | Viewing angle, vertical: 56° | Length: 215.2 mm | Compatible memory cards: MicroSD (TransFlash) | Supported graphics resolutions: 1280 x 720 (HD 720) | Ethernet LAN: Yes | Angle of rotation: 360° | Reset button: Yes | Compatible memory cards: MicroSDHC | Operating temperature (T-T): -30 - 60 °C | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | Supported graphics resolutions: 640 x 480 (VGA) | Video formats supported: M-JPEG | Video formats supported: H.265 | Compatible memory cards: MicroSDXC | Package weight: 1 kg | Video formats supported: H.264 | Video formats supported: H.264+ | Width: 78.8 mm | Height: 78.6 mm | Storage relative humidity (H-H): 0 - 95% | Video formats supported: H.265+ | Power source type: DC, PoE | Package width: 137 mm | Power consumption (max): 7.2 W | Operating relative humidity (H-H): 0 - 95% | Ethernet interface type: Fast Ethernet | Pan range: 0 - 360° | Total megapixels: 2 MP | Storage temperature (T-T): -30 - 60 °C | Package depth: 315 mm | Type: IP security camera | Number of cameras: 1 | Weight: 680 g | Bit rate: 32 Kbps - 8 Mbps | International Protection (IP) code: IP67 | Supported graphics resolutions: 320 x 240 | Supported graphics resolutions: 640 x 360 | Package height: 141 mm | Networking standards: IEEE 802.3af | Card reader integrated: Yes | Supported video modes: 360p | Built-in HDD: No | Progressive scan: Yes | Supported video modes: 1080p | Noise reduction: Yes | Supported video modes: 240p | Frame rate: 30 fps | Camera shutter speed: 1/3 - 1/100000 s | Optical sensor size: 25.4 / 2.8 mm (1 / 2.8") | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Signal-to-Noise Ratio (SNR): 120 dB | Day/night mode: Yes | Maximum aperture number: 1 | Video compression formats: H.265 | Video compression formats: H.264+ | DC output current: 0.6 A | Privacy masking: Yes | Number of sensors: 1 | Languages support: Multi | Gain control type: Auto | Noise reduction technology: 3D noise reduction | Heartbeat: Yes | Image quality adjustment: Saturation | Placement supported: Outdoor | Image quality adjustment: Sharpness | Web browser: Yes | Sensor type: CMOS | Fixed focal length: 2.8 mm | Region of Interest (ROI) encoding: Yes | Camera pan control: Yes | Video streaming: Yes | Number of users: 32 user(s) | Image quality adjustment: Brightness | IP address filtering: Yes | DC output voltage: 12 | Mounting type: Wall | Number of languages: 33 | Mirror: Yes | Night vision: Yes | Active tampering alarm: Yes | Power consumption (Power over Ethernet (PoE)): 8.5 W | Password protection: Yes | Video compression formats: H.265+ | Video compression formats: H.264 | Number of lenses: 1 | Maximum memory card size: 256 GB | HTTPS encryption: Yes | Viewing angle, diagonal: 127° | Image quality adjustment:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

Contrast | Video compression formats: M-JPEG | Camera tilt control: Yes | Behavior analysis: Intrusion detection, Line crossing detection, Region entrance detection, Region exiting detection | Anti-flicker: Yes | Image quality adjustment: Colour depth | Motion sensor: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903