



HIKVISION IP CAMERA DS- 2CD1041G2-LIU 2.8MM EN



Modelis: DS-2CD1041G2-LIU 2.8mm PL

Gamintojas: HIKVISION

EAN: 6936422117207

Prekės kodas: 361358

62.99€

PoE standard: IEEE 802.3af | Lens viewing angle, diagonal: 114° | Lens viewing angle, horizontal: 98° | Mono sound: Yes | Sustainability certificates: RoHS | Lens viewing angle, vertical: 54° | Sustainability certificates: WEEE | Ethernet LAN data rates: 10,100 Mbit/s | Power over Ethernet (PoE): Yes | Width: 216 mm | Operating relative humidity (H-H): 0 - 95% | Package weight: 481 g | Operating temperature (T-T): -30 - 60 °C | International Protection (IP) code: IP67 | Number of cameras: 1 | Web-based management: Yes | Type: IP security camera | Storage relative humidity (H-H): 0 - 95% | Ethernet LAN (RJ-45) ports: 1 | Package height: 69 mm | Maximum resolution: 2560 x 1410 pixels | Tilt angle range: 0 - 90° | Connectivity technology: Wired | Housing material: Plastic | Housing material: Metal | Package width: 171 mm | Product colour: White | Sensor type: CMOS | Minimum illumination: 0.005 lx | Package depth: 66 mm | Depth: 121 mm | Storage temperature (T-T): -30 - 60 °C | Quality of Service (QoS) support: Yes | Warnings: The product contains electronic components do not dispose of with the normal household waste. | Signal-to-Noise Ratio (SNR): 52 dB | Ethernet LAN: Yes | Angle of rotation: 360° | Weight: 270 g | Recognize distance (wide): 12 m |

Progressive scan: Yes | Bit rate: 32 Kbps - 8 Mbps | Warnings: Avoid direct contact with water to

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Height: 118 mm | Video compression formats: H.265+ | Video compression formats: H.264 | DC output current: 0.4 A | LED type: IR | Maximum aperture number: 1.6 | Day/night mode: Yes | Observe distance (wide): 25 m | Video compression formats: H.264+ | Wide Dynamic Range (WDR): 120 dB | Video compression formats: M-JPEG | Video compression formats: H.265 | Highlight Compensation (HLC): Yes | Built-in microphone: Yes | Pan range: 0 - 360° | Detect distance (wide): 63 m | Total megapixels: 4 MP | Region of Interest (ROI) encoding: Yes | Camera shutter speed: 1/3 - 1/100000 s | Client interoperability: ONVIF (Profile S / (Profile T / (Profile G), ISAPI, SDK | Optical sensor size: 25.4 / 3 mm (1 / 3") | Night vision distance: 30 m | Number of lenses: 1 | Password protection: Yes | Infra-red wavelength: 850 nm | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Identify distance (wide): 6 m | Power management: DC 12 V | Number of users: 32 user(s) | Video motion detection: Yes | Sample rate: 8 kHz / 16 kHz | Maximum power: 5 W | Heartbeat: Yes | Mirror: Yes | Night vision: Yes | Noise filter: Y

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903