



Hikvision Digital Technology DS- 2CD2723G2-IZS Outdoor IP Security Camera Earphones 1920 x 1080 px Ceiling Wall



Modelis: DS-2CD2723G2-IZS (2.8-12mm)

Gamintojas: HIKVISION

EAN: 6941264070818

Prekės kodas: 361362

118.99€

Connectivity technology: Wired | Tilt angle range: 0 - 75° | Audio output channels: 1 channels | Ethernet LAN (RJ-45) ports: 1 | Bluetooth: No | Package weight: 1.42 kg | Operating relative humidity (H-H): 0 - 95% | Form factor: Dome | Weight: 880 g | Package width: 244 mm | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1280 x 720 (HD 720) | Type: IP security camera | Networking standards: IEEE 802.3af | Power consumption (max): 10.5 W | Networking standards: IEEE 802.1x | Operating temperature (T-T): -30 - 60 °C | Web-based management: Yes | Maximum resolution: 1920 x 1080 pixels | Reset button: Yes | Power source type:

DC, PoE | Supported graphics resolutions: 640 x 360 | Supported graphics resolutions: 1920 x 1080

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be

išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(HD 1080) | Package height: 173 mm | Package depth: 174 mm | Product colour: White | Quality of Service (QoS) support: Yes | Compatible memory cards: MicroSD (TransFlash) | Heartbeat: Yes | IK code: IK10 | Observe distance (wide): 54.7 m | Image quality adjustment: Saturation | Focal length range: 2.8-12 mm | Region of Interest (ROI) encoding: Yes | LED type: IR | Noise reduction: Yes | Video compression formats: H.264+ | DC output voltage: 12 | Built-in HDD: No | Anti-flicker: Yes | Video compression formats: H.265+ | Image quality adjustment: Brightness | Maximum aperture number: 1.6 | Compatible memory cards: MicroSDXC | Video compression formats: H.264 | Image quality adjustment: Sharpness | Sample rate: 48 kHz | Compatible memory cards: MicroSDHC | Video compression formats: H.265 | Detect distance (wide): 137.9 m | Day/night mode: Yes | Total megapixels: 2 MP | Gain control type: Auto | Night vision distance: 40 m | International Protection (IP) code: IP67 | IP address filtering: Yes | Bit rate: 32 Kbps - 8 Mbps | Recognize distance (wide): 27.5 m | Voice codecs: G.711alaw | Number of lenses: 1 | Camera shutter speed: 1/3 - 1/100000 s | Card reader integrated: Yes | HTTPS encryption: Yes | Housing material: Metal | Warnings: The product contains electronic components do not dispose of with the normal household waste. | Voice codecs: G.726 | Password protection: Yes | Housing material: Plastic | Voice codecs: G.711ulaw | Optical sensor size: 25.4 / 2.8 mm (1 / 2.8") | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Infra-red wavelength: 850 nm | Identify distance (wide): 13.8 m | Noise reduction technology: 3D noise reduction | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Audio input channels: 1 channels | Voice codecs: MP2L2 | Wi-Fi: No | Voice codecs: AAC | Number of languages: 33 | Pan range: 0 - 355° | Back Light Compensation (BLC): Yes | Angle of rotation: 355° | Infrared (IR) cut-off filter: Yes | Camera pan control: Yes | Progressive scan: Yes | Placement supported: Outdoor | Voice codecs: G.722.1 | Video streaming: Yes | Night vision: Yes | Maximum memory card size: 256 GB | Image quality adjustment: Contrast | Image quality adjustment: Mirror | Height: 111.6 mm | Video motion detection: Yes | Video compression formats: M-JPEG | Ethernet LAN: Yes | Sensor type: CMOS | Camera tilt control: Yes | Frame rate: 30 fps | Behavior analysis: Intrusion detection, Line crossing detection | Ethernet interface type: Fast Ethernet | Number of cameras: 1 | Number of sensors: 1 | Diameter: 15.3 cm | Voice codecs: PCM | Web browser: Yes | Wide Dynamic Range (WDR): Yes | Power consumption (Power over Ethernet (PoE)): 12.5 W | Mounting type: Ceiling/wall | Highlight Compensation (HLC): Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903