



HIKVISION IP CAMERA DS- 2CD1183G2-LIUF 2.8mm



Modelis: DS-2CD1183G2-LIUF 2.8mm PL

Gamintojas: HIKVISION

EAN: 6936422114695

Prekės kodas: 361366

103.99€

Form factor: Dome | Web-based management: Yes | Supported graphics resolutions: 3200 x 1800 | Bluetooth: No | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 3860 x 2160 | Package weight: 800 g | Ethernet LAN (RJ-45) ports: 1 | Type: IP security camera | Product colour: White | Tilt angle range: 0 - 75° | Maximum resolution: 3840 x 2160 pixels | Package width: 150 mm | Operating relative humidity (H-H): 0 - 95% | Storage temperature (T-T): -30 - 60 °C | Connectivity technology: Wired | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 2688 x 1512 | Operating temperature (T-T): -30 - 60 °C | Quality of Service (QoS) support: Yes | Storage relative humidity (H-H): 0 - 95% | Supported graphics resolutions: 640 x 360 | Supported graphics resolutions: 640 x 480 (VGA) | Built-in microphone: Yes | Power source type: DC, PoE | Power consumption (max): 6 W | Weight: 550 g | Lens mount interface: M12 | Password protection: Yes | Noise reduction technology: 3D noise reduction | Compliance certificates: KC | Detect distance: 79 m | Supported network protocols: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP, UPnP | Audio formats supported: AAC-LC | Compatible memory cards: MicroSDXC | Mirror: Yes | Compliance certificates: CB | Night vision: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

išsijyiant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Wi-Fi: No | Image quality adjustment: Brightness | Number of languages: 2 | Client interoperability: iVMS-4200, Hik-Connect | Compliance certificates: Federal Communications Commission (FCC) | Number of simultaneous live view channels: 6 channels | Camera shutter speed: 1/3 - 1/100000 s | User access level: Administrator, Operator, User | Audio formats supported: G.722.1 | Sensor type: CMOS | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Pan range: 0 - 355° | Infrared (IR) cut-off filter: Yes | Total megapixels: 8 MP | Progressive scan: Yes | Compliance certificates: Low Voltage Directive (LVD) | Placement supported: Indoor & outdoor | Ethernet LAN: Yes | Audio formats supported: PCM | Audio formats supported: MP2L2 | Video recording: Yes | Heartbeat: Yes | Bit rate range: 16 - 160 Kbit/s | Night vision distance: 30 m | Weatherproof: Yes | Card reader integrated: Yes | Number of lenses: 1 | Bit rate: 32 Kbps - 16 Mbps | Package height: 141 mm | Signal-to-Noise Ratio (SNR): 52 dB | DC output voltage: 12 | Back Light Compensation (BLC): Yes | Active tampering alarm: Yes | Noise reduction: Yes | Minimum illumination: 0 lx | Maximum memory card size: 512 GB | Angle of rotation: 355° | Audio formats supported: G.726 | IK code: IK08 | Audio formats supported: G.711 A-law | Height: 97.6 mm | Image quality adjustment: Contrast | Image quality adjustment: Saturation | Image quality adjustment: White balance | Wide Dynamic Range (WDR): Yes | Highlight Compensation (HLC): Yes | Compatible memory cards: MicroSD (TransFlash) | Sample rates: 8 - 16 kHz | Observe distance: 31 m | Lens viewing angle, diagonal: 134° | Power consumption (Power over Ethernet (PoE)): 7.5 W | Package depth: 150 mm | Diameter: 12.2 cm | Mounting type: Ceiling | Iris: Yes | Lens viewing angle, vertical: 62° | International Protection (IP) code: IP67 | Lens viewing angle, horizontal: 113° | Compliance certificates: WEEE | Compliance certificates: RoHS | Number of cameras: 1 | Number of sensors: 1 | Compatible memory cards: MicroSDHC | Image quality adjustment: Sharpness | Compliance certificates: REACH | Housing material: Metal | Dynamic range: 120 dB | Identify distance: 7 m | Fixed focal length: 2.8 mm | Frame rate: 15 fps | Digital watermark: Yes | DC output current: 0.5 A | Video compression formats: H.264 | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Housing material: Plastic | Password reset via email: Yes | Maximum aperture number: 2 | Video compression formats: H.265+ | Video compression formats: H.265 | Region of Interest (ROI) encoding: Yes | Live view: Yes | Video compression formats: M-JPEG | Video compression formats: H.264+ | Infra-red wavelength: 850 nm | Day/night mode: Yes | Built-in HDD: No | Recognize distance: 15 m | Video motion detection: Yes | Privacy masking: Yes | Number of users: 32 user(s) | LED type: IR

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903