Reolink E Series E540 - IP camera, black

Modelis: E-Series-E540-B

Gamintojas: REOLINK

EAN: 6975253984336

Prekės kodas: 361385

109.99€

Packaging content: 1* E Series E540-B 1* Security Bracket 1* Strap 1* Power Adapter 1* Reset Needle 1* Pack of Screws 1* 4.5m Power Extension Cable 1* 1m Network Cable 1* Mounting Template 1* Quick Start Guide 1* Surveillance Sticker | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11b | Audio system: 2-way | Security algorithms: WPA2 | Security algorithms: WPA | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Lens viewing angle, vertical: 37 - 68° | Product colour: Black | Human and vehicle targets classification: Yes | Connectivity technology: Wired & Wireless | Built-in microphone: Yes | Power source type: DC | Tilt angle range: 0 - 50° | Supported graphics resolutions: 2560 x 1920 | User access level: Administrator, User | Bluetooth: No | Weight: 415 g | Reset button: Yes | Maximum resolution: 2560 x 1920 pixels | DC-in jack: Yes | Form factor: Spherical | Number of sensors: 1 | International Protection (IP) code: IP65 | Wi-Fi: Yes | Bit rate: 64 Kbps - 5120 Kbps | LED type: IR/White | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11a | Wi-Fi standards: 802.11b | Number of users: 20 user(s) | Lens viewing angle, horizontal: 48 - 90° | Power consumption (max): 12 W | Built-in HDD: No | Wi-Fi standards: Wi-Fi 4 (802.11n) | Focal length range: 2.8 - 8 mm | Number of cameras: 1 | Diameter: 9 cm | DC output current: 1 A | Card reader integrated: Yes | Mobile operating systems supported:

Android | Number of lenses: 1 | Video streaming: Yes | Virtual assistant: Google Assistant | Mounting type: Ceiling | Pan range: 0 - 355° | Operating relative humidity (H-H): 10 - 90% | Ethernet interface type: Fast Ethernet | Video formats supported: H.264 | Number of illumination LEDs: 12 | Video recording: Yes | Total megapixels: 5 MP | Compatible memory cards: MicroSD (TransFlash) | Live view: Yes | Placement supported: Indoor & outdoor | Height: 120 mm | Mac operating systems supported: Yes | Mounting kit: Yes | DC output voltage: 12 | Built-in speaker(s): Yes | Operating temperature (T-T): -10 - 50 °C | Windows operating systems supported: Yes | Ethernet LAN: Yes | Video compression formats: H.264 | Frame rate: 20 fps | Ethernet LAN (RJ-45) ports: 1 | Manual: Yes | Maximum aperture number: 1.6 | Supported network protocols: HTTPS, SSL, TCP/IP, UDP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P | Sensor type: CMOS | Video motion detection: Yes | Mobile operating systems supported: iOS | Type: IP security camera | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Infra-red wavelength: 850 nm | Infrared (IR) cut-off filter: Yes | Screws included: Yes | Night vision: Yes | Maximum memory card size: 256 GB | Night vision distance: 12 m