

MSI Spatium S270 SATA 2.5 480GB 2.5" Serial ATA III 3D NAND

Gamintojas: **MSI** · Modelis: **S78-440E350-P83** · EAN: **4711377001168** · Prekės kodas: **361554**



99,90 €

Kaina su PVM

Be PVM: **82,56 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ SATA III interface
- ✓ Sequential Read speeds up to 500MB/s and Write speeds up to 450MB/s
- ✓ Up to 500 TBW
- ✓ Built-in data security and error-correction capabilities
- ✓ 120GB to 960GB capacities in 2.5" SATA form factor
- ✓ Suitable for both desktop and notebook



Aprašymas

CHARGING AHEAD WITH SPEED

From the MSI universe comes storage with blazing speeds and incredible performance. Take your system to the next level with SPATIUM.

A NEED FOR SPEED!

Optimized for the SATA III interface, SPATIUM S270 SSD reaches read/write speeds up to 500/450 MB/s, allowing for rapid data transfer and shortened game load times.

SMALL SIZE, MORE STORAGE

The latest 3D NAND flash technology brings dense storage in a compact design and allows SPATIUM storage capacities up to 960GB.

DON'T**STOP GAMING**

Built-in data security and error-correction capabilities extend the endurance and longevity of the NAND flash storage.

TAKE CARE**OF YOUR DATA**

Migrate your data, monitor drive health and performance metrics in real-time with MSI Center. Prevent loss of data using the provided Actiphy software solution which includes backup & restore functionality.

5-YEAR**WARRANTY**

MSI stands by the quality and reliability of the SPATIUM S270 with a 5-Year comprehensive warranty. If you need assistance or are not satisfied with your product, MSI support is available to help and assist.

Techninė specifikacija

Specifications	
Sandėlio grupė	IT > Drives and accessories > SSDs [+0][-0]
Features	
SSD capacity	480 GB
SSD form factor	2.5"
Interface	Serial ATA III
NVMe	No
Memory type	3D NAND
Component for	PC/Laptop
Data transfer rate	6 Gbit/s
Write speed	450 MB/s
Random read (4KB)	55000 IOPS
Random write (4KB)	80000 IOPS
S.M.A.R.T. support	Yes
TRIM support	Yes
ECC	Yes
Mean time between failures (MTBF)	2000000 h
Power	
Power consumption (max)	2 W
Weight & dimensions	
Width	69.8 mm
Depth	100.2 mm
Height	7 mm

Operational conditions

Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C

Matmenys ir svoris

Matmenys (I × P × A)	13,00cm × 2,00cm × 11,00cm
Svoris	0,07kg