



Cudy GS108 network switch Gigabit Ethernet (10/100/1000) Black



Modelis: GS108

Gamintojas: CUDY

EAN: 6971690790554

Prekės kodas: 363360

18.98€

Cable types supported: Cat8 | Rack mounting: No | Packet buffer memory: 2.5 MB | Storage temperature (T-T): -40 - 70 °C | Auto MDI/MDI-X: Yes | Switching capacity: 16 Gbit/s | MAC address auto-aging supported: Yes | Width: 137 mm | Jumbo frames support: Yes | MAC address table: 1000 entries | Cable types supported: Cat7 | MAC address auto-learning supported: Yes | Cable types supported: Cat6+ | Throughput: 11.9 Mpps | Cable types supported: Cat5 | Cable types supported: Cat5e | Package depth: 120 mm | Package type: Box | VLAN support: Yes | Copper ethernet cabling technology: 1000BASE-TX | Quick start guide: Yes | DC input voltage: 5 V | Master (outer) case height: 400 mm | Master (outer) case width: 505 mm | Cable types supported: Cat6e | Cable types supported: Cat7e | Master (outer) case length: 320 mm | Package height: 63 mm | Cable types supported: Cat4 | Power over Ethernet (PoE): No | Cables included: DC | Cable types supported: Cat6a | Cable types supported: Cat6 | Cable types supported: Cat8.1 | Package width: 175 mm | Jumbo frames: 2000 | Basic switching RJ-45 Ethernet ports quantity: 8 | Product colour: Black |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Master (outer) case gross weight: 21 kg | Power supply included: Yes | Operating temperature (T-T): -10 - 50 °C | Copper ethernet cabling technology: 10BASE-T | Store-and-forward: Yes | Half duplex: Yes | Auto-negotiation: Yes | Weight: 300 g | Height: 25 mm | Products per master (outer) case: 40 pc(s) | Power source: AC/DC | Cable types supported: Cat3 | Warnings: Do not open the case or try to repair it yourself. | AC input voltage: 100 - 240 V | LED indicators: Link | Mean time between failures (MTBF): 100000 h | Ethernet LAN data rates: 10,100,1000 Mbit/s | Copper ethernet cabling technology: 100BASE-TX | Operating altitude: 0 - 3048 m | Flow control support: Yes | Depth: 77 mm | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | LED indicators: Loop | Full duplex: Yes | LED indicators: Power | Package weight: 500 g | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3x

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903