

Cudy GS1005P network switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey

Gamintojas: CUDY · Modelis: GS1005P · EAN: 6971690790998 · Prekės kodas: 363361



38,90 €

Kaina su PVM

Be PVM: 32,15 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4x GbE with 802.3at/af Mode A PoE
- ✓ 1x Uplink GbE
- ✓ 60W Power Supply
- ✓ Default/VLAN/Extend Modes
- ✓ Watchdog On/Off
- ✓ PoE Max Status LED
- ✓ Desktop, Wall-Mount
- ✓ 119×85×28 mm (4.69×3.35×1.1")



Aprašymas

Reliable PoE for 24/7 Consistent Operation

IEEE 802.3at/af. Up to 30W Per Port.

Each PoE port delivers up to 30W of power, making it suitable for access points, IP cameras, digital signage, and most other PoE devices.

PoE Auto Recovery

Watchdog will be enabled under VLAN and Extend modes, and if a connected device freezes and stops transmitting data for 5 minutes, the Watchdog will automatically reboot the corresponding PoE port.

PoE Management Made Simple

Extend PoE Reach. Enhance Client Security.

Extend for 250 m Transmission

For long-distance networking, enable the Extend mode to connect clients up to 250 meters away by limiting the port speed to 10 Mbps.

VLAN Isolates Downlink Ports for Improved Safety

Turn on the VLAN mode to prevent client-side hacking, preventing sensitive data from leaking. The downlink clients will only be able to communicate with the uplink devices.

Easy Installation. Robust Protection.

Plug and Play

Connect your router to the uplink port, client devices to PoE ports, and power on the PoE switch—then you're good to go.

Fit into a Distribution Box

Fits easily into most distribution boxes and makes cable management a breeze.

Protect Clients with Outstanding EMC

Shield your cameras and access points, from surges in power grid and ESD, delivering rock-solid reliability.

ESD: Contact 6kV; Air 8kV

Surge: Power DM 2kV, CM 4kV; RJ45 CM 4kV

Metal Casing. Wallmount Ready.

Metal casing delivers simplicity and protection for the network hub. Need to save floor spaces? The wall-mounting kit is included in the box to help you.

Versatile Scenarios

Surveillance

Office Networking

Campuses Wi-Fi

Accesses and Signages

Techninė specifikacija

Specifications

Sandėlio grupė Enterprise and server products > KVM > Switches [+0][-0]

Management features

Switch type Unmanaged

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Uplink ports quantity	1

Power connector	DC-in jack
Network	
Networking standards	IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3i, IEEE 802.3x
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Flow control support	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Data transmission	
MAC address table	2048 entries
Switching capacity	10 Gbit/s
Forwarding rate	7.44 Mpps
Design	
Product colour	Grey
Housing material	Metal
LED indicators	Activity, Link, PoE, Power
Performance	
Plug and Play	Yes
Power	
Power source	DC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	1.25 A
Input voltage	52 V
Power consumption (typical)	5 W
Power consumption (max)	60 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	4
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	60 W
Other features	
Warranty period	1 year(s)
Operational conditions	
Operating temperature (T-T)	0 - 40 °C

Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 95%
Weight & dimensions	
Width	119 mm
Depth	85 mm
Height	28 mm
Weight	261 g
Packaging content	
Cables included	AC, DC
User guide	Yes
Rack mount kit	Yes
Packaging data	
Package type	Box
Package width	186 mm
Package depth	123 mm
Package height	81.5 mm
Package weight	784 g
Logistics data	
Country of origin	China
Matmenys ir svoris	
Matmenys (I × P × A)	9,00cm × 19,00cm × 13,00cm
Svoris	0,80kg