



# Cudy GS1005P network switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey



Modelis: GS1005P

Gamintojas: CUDY

EAN: 6971690790998

Prekės kodas: 363361

## 40.99€

Flow control support: Yes | Forwarding rate: 7.44 Mpps | Power over Ethernet plus (PoE+) ports quantity: 4 | Switch type: Unmanaged | Power connector: DC-in jack | MAC address table: 2048 entries | Rack mount kit: Yes | Warranty period: 1 year(s) | Uplink ports quantity: 1 | User guide: Yes | Operating temperature (T-T): 0 - 40 °C | Power consumption (typical): 5 W | Total Power over Ethernet (PoE) budget: 60 W | LED indicators: Power | AC input voltage: 100 - 240 V | LED indicators: Link | Storage temperature (T-T): -40 - 70 °C | LED indicators: PoE | Input current: 1.25 A | Package depth: 123 mm | LED indicators: Activity | Product colour: Grey | Switching capacity: 10 Gbit/s |

Depth: 85 mm | Weight: 261 g | Plug and Play: Yes | Power consumption (max): 60 W | Networking

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

standards: IEEE 802.3af | Networking standards: IEEE 802.3x | Operating relative humidity (H-H): 10 - 90% | Package width: 186 mm | Housing material: Metal | Power over Ethernet (PoE): Yes | Width: 119 mm | Input voltage: 52 V | Ethernet LAN data rates: 10,100,1000 Mbit/s | AC input frequency: 50/60 Hz | Cables included: DC | Package weight: 784 g | Height: 28 mm | Power supply included: Yes | Power source: DC | Basic switching RJ-45 Ethernet ports quantity: 5 | Copper ethernet cabling technology: 1000BASE-T | Copper ethernet cabling technology: 10BASE-T | Package type: Box | Copper ethernet cabling technology: 100BASE-TX | Cables included: AC | Package height: 81.5 mm | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3at | Storage relative humidity (H-H): 10 - 95% | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Do not open the case or try to repair it yourself.