



TP-Link CPE210 300 Mbit/s White Power over Ethernet (PoE)



Modelis: CPE210

Gamintojas: TP-LINK

EAN: 6935364071677

Prekės kodas: 363416

46.98€

Certification: CE/FCC/UL/IC/GS/PSB/C-tick/SAA/S-Mark/KC-mark CE, FCC, RoHS | Output voltage: 24 V | International Protection (IP) code: IPX5 | Service Set Identifier (SSID) features: SSID broadcast | Cables included: AC | Service Set Identifier (SSID) features: SSID broadcast on/off | Height: 60 mm | Universal Plug and Play (UPnP): Yes | Width: 224 mm | Maximum outdoor range: 5000 m | Automatic channel selection: Yes | Package width: 132 mm | Placement: Pole | Package height: 106 mm | Polarization: Dual polarization | Flash memory: 8 MB | Antenna direction type: Directional | Automatic channel scanning: Yes | VLAN support: Yes | Dynamic Frequency Selection (DFS): Yes | IGMP snooping: Yes | Wireless isolation: Yes | Depth: 79 mm | Built-in processor: Yes | 6 GHz: No | Processor architecture: MIPS 74Kc | Auto Wireless Distribution System (WDS): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Package depth: 270 mm | Output current: 0.25 A | Internal memory: 64 MB | Quantity per pack: 1 pc(s) | Management platform: Pharos Control | Firmware upgradeable: Yes | Product colour: White | 2.4 GHz: Yes | Operating temperature (T-T): -30

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- 70 °C | DC-in jack: Yes | Antenna type: Internal | Networking standards: IEEE 802.11b | Security algorithms: WPA2 | Processor model: Qualcomm Atheros | Operating relative humidity (H-H): 10 - 90% | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: AES | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Storage relative humidity (H-H): 5 - 95% | Security algorithms: WPA-PSK | MIMO: Yes | LED indicators: Status | AC input voltage: 100 - 240 V | Security algorithms: TKIP | Maximum data transfer rate: 300 Mbit/s | Ethernet LAN (RJ-45) ports: 2 | Security algorithms: WPA | Reset button: Yes | AC input frequency: 50 - 60 Hz | Antenna gain level (max): 9 dBi | 5 GHz: No | Power over Ethernet (PoE): Yes | Processor frequency: 560 MHz | Storage temperature (T-T): -40 - 70 °C | Mounting kit: Yes | Package weight: 760 g | Frequency band: 2.4 - 2.483 GHz

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903