



# TP-Link Omada AC1750 Wireless MU-MIMO Gigabit Ceiling Mount Access Point



Modelis: TL-EAP245

Gamintojas: TP-LINK

EAN: 6935364096663

Prekės kodas: 363417

## 103.00€

Compatible operating systems: Microsoft Windows XP, Windows Vista, Windows 7, Windows 8, Windows 10 | Operating relative humidity (H-H): 10 - 90% | Mounting kit: Yes | Automatic channel selection: Yes | Antenna features: Integrated antenna | Operating temperature (T-T): 0 - 40 °C | Security algorithms: WPA | Band steering: Yes | Width: 180 mm | Wi-Fi Multimedia (WMM)/(WME): Yes | Security algorithms: 128-bit WEP | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Package height: 65 mm | Number of SSID supported: 16 | Maximum data transfer rate (2.4 GHz): 450 Mbit/s | Port-based Network Access Control (PNAC): Yes | Management protocols: HTTP/HTTPS | Security algorithms: 152-bit WEP | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Harmonized System (HS) code: 85176990 | Ethernet LAN (RJ-45) ports: 2 | Security algorithms: WPA2-PSK | Power over Ethernet (PoE): Yes | Height: 47.5 mm | Rate limiting: Yes | Output voltage: 12 V | Package width: 228 mm | Transmitting power (CE): 20 - 23 dBm |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Sustainability compliance: Yes | Transmitting power (FCC): 24 dBm | Quantity per pack: 1 pc(s) | Power consumption (typical): 12.7 W | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power over Ethernet (PoE) type supported: Passive PoE | Placement: Ceiling, Wall | Output current: 1.5 A | LED indicators: Power | Access Control List (ACL): Yes | Cable lock slot type: Kensington | Wireless isolation: Yes | Package depth: 340 mm | Virtual LAN features: SSID-based VLAN assignment | Package weight: 1.18 kg | Cables included: AC | Depth: 180 mm | Automatic channel scanning: Yes | Cabling technology: 10/100/1000Base-T(X) | Airtime Fairness (ATF): Yes | MIMO type: Multi User MIMO | Antenna gain level (max): 4 dBi | BeamForming: Yes | Maximum data transfer rate (5 GHz): 1300 Mbit/s | 6 GHz: No | Antenna direction type: Omni-directional | VLAN support: Yes | Service Set Identifier (SSID) features: Multiple SSIDs | Quick start guide: Yes | Syslog: Yes | Power over Ethernet (PoE) type supported: Active PoE | PoE adapter included: Yes | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3af | Warnings: Electronic products should be recycled at specialist electronic waste collection facilities. | Networking standards: IEEE 802.11ac | Compliance certificates: RoHS | Compliance certificates: CE | Frequency band: 2.4 - 5 GHz | Warnings: Do not expose to prolonged moisture. | Warnings: Avoid direct contact with water. | Compliance certificates: Federal Communications Commission (FCC) | Reset button: Yes | Product colour: White | Antenna type: Internal | Cable lock slot: Yes | Networking standards: IEEE 802.11n | Transmitting power: 27 dBmW | Ethernet LAN data rates: 1000 Mbit/s | 5 GHz: Yes | Maximum data transfer rate: 1750 Mbit/s | MIMO: Yes | 2.4 GHz: Yes | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 10

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903