TP-Link Omada EAP225-Outdoor 1200 Mbit/s White Power over Ethernet (PoE)

Modelis: EAP225-OUTDOOR

Gamintojas: TP-LINK

EAN: 6935364083571

Prekės kodas: 363429

86.99€

Compatible operating systems: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux | Transmitting power (CE): 27 dBm | Transmitting power (FCC): 22 dBm | 6 GHz: No | Sustainability compliance: Yes | BeamForming: Yes | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN data rates: 1000 Mbit/s | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Mounting kit: Yes | Antenna direction type: Omni-directional | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3af | Antennas quantity: 2 | Frequency band: 2.4 - 5 GHz | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.3ab | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: 802.1x RADIUS | Reset button: Yes | Antenna type: External | Antenna features: Detachable antenna | Ethernet LAN data rates: 100 | Maximum data

transfer rate: 1200 Mbit/s | Placement: Pole, Wall | Package width: 140 mm | Quick start guide: Yes | Ethernet LAN (RJ-45) ports: 1 | 2.4 GHz: Yes | Operating temperature (T-T): -30 - 70 °C | Package height: 100 mm | 5 GHz: Yes | Package depth: 270 mm | Package weight: 640 g | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.11ac | Ethernet LAN data rates: 10 | Product colour: White | AC adapter included: Yes | Power over Ethernet (PoE): Yes | Antenna gain level (max): 4 dBi | Maximum data transfer rate (5 GHz): 867 Mbit/s | Quantity per pack: 1 pc(s) | Power consumption (typical): 10.5 W | Airtime Fairness (ATF): Yes | Height: 27 mm | VLAN support: Yes | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | Depth: 46 mm | Virtual LAN features: VLAN mapping | Syslog: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Number of SSID supported: 16 | Rate limiting: Yes | Power over Ethernet (PoE) type supported: Passive PoE | Service Set Identifier (SSID) features: Multiple SSIDs | Output voltage: 24 V | International Protection (IP) code: IP65 | Band steering: Yes | Access Control List (ACL): Yes | Width: 215 mm | Harmonized System (HS) code: 85176990 | MIMO type: Multi User MIMO | Compliance certificates: RoHS | Compliance certificates: CE | Warnings: Avoid direct contact with water. | Warnings: Electronic products should be recycled at specialist electronic waste collection facilities. | Warnings: Do not expose to prolonged moisture. | Compliance certificates: Federal Communications Commission (FCC)