



TP-Link Omada AX1800 Ceiling Mount WiFi 6 Access Point



Modelis: EAP613

Gamintojas: TP-LINK

EAN: 4895252500516

Prekės kodas: 363433

94.99€

Compatible operating systems: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux | Certification: CE, FCC, RoHS | Wireless isolation: Yes | Airtime Fairness (ATF): Yes | Automatic channel selection: Yes | DC voltage range: 12 V | Rate limiting: Yes | Automatic channel scanning: Yes | Band steering: Yes | Power over Ethernet (PoE) type supported: Passive PoE | Management platform: Omada | MIMO type: Multi User MIMO | Warnings: Do not expose to prolonged moisture. | BeamForming: Yes | Warnings: Electronic products should be recycled at specialist electronic waste collection facilities. | Warnings: Avoid direct contact with water. | Transmitting power (CE): 20 dBm(2.4 GHz, EIRP) 23 dBm(5 GHz band1/2, EIRP) 25 dBm (5 GHz band3) | 6 GHz: No | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11ax | Transmitting power (FCC): 25 dBm (2.4 GHz) 25 dBm (5 GHz) | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11a | Web-based management: Yes | Networking standards: IEEE 802.11ac | 2.4 GHz: Yes | Frequency band: 2.4 - 5 GHz | LED indicators: Yes | Antenna gain level (max): 5 dBi | Maximum data transfer rate (5 GHz): 1201 Mbit/s | Spread spectrum method: OFDMA | MIMO: Yes | Reset button: Yes | Operating relative humidity (H-H): 0 -

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

40% | Product colour: White | 5 GHz: Yes | Antenna type: Internal | Placement: Ceiling, Wall |
Maximum data transfer rate: 1775 Mbit/s | Quantity per pack: 1 pc(s) | Input current: 1 A | Power
consumption (typical): 9.6 W | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN data rates: 100 |
Wi-Fi Multimedia (WMM)/(WME): Yes | Mounting kit: Yes | VLAN support: Yes | Height: 33.6 mm |
Antennas quantity: 4 | Quick start guide: Yes | Power consumption (max): 10.6 W | DC-in jack: Yes |
Security algorithms: HTTPS | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% |
Security algorithms: WPA2 | Security algorithms: SNMPv2 | Storage temperature (T-T): -40 - 70 °C |
Operating temperature (T-T): 10 - 90 °C | Power over Ethernet (PoE): Yes | Width: 160 mm | Ethernet
LAN (RJ-45) ports: 1 | Maximum data transfer rate (2.4 GHz): 574 Mbit/s | Number of SSID supported:
16 | Security algorithms: WPA | Security algorithms: SNMPv3 | Security algorithms: SNMP | Depth:
160 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903