TP-Link EAP113-Outdoor 300 Mbit/s White Power over Ethernet (PoE)

Modelis: TL-EAP113-OUTDOOR

Gamintojas: TP-LINK

EAN: 4895252503494

Prekės kodas: 363434

44.99€

Certification: CE, FCC, RoHS | 2.4 GHz: Yes | DC voltage range: 48 V | Security algorithms: SSH | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Operating temperature (T-T): -30 - 65 °C | Number of SSID supported: 8 | Transmitting power (CE): 20 dBm | Security algorithms: WPA | Networking standards: IEEE 802.11b | Operating relative humidity (H-H): 10 - 90% | Security algorithms: 128-bit WEP | Security algorithms: SNMP | Syslog: Yes | Sustainability compliance: Yes | Access Control List (ACL): Yes | Rate limiting: Yes | Transmitting power (FCC): 22 dBm | Antennas quantity: 2 | Service Set Identifier (SSID) features: Multiple SSIDs | International Protection (IP) code: IP65 | Antenna included: Yes | Width: 214.9 mm | Security algorithms: 64-bit WEP | Security algorithms: WPA2-Enterprise | Security algorithms: SNMPv2 | Security algorithms: 152-bit WEP | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Power over Ethernet (PoE) type supported: Passive PoE | MAC address filtering: Yes | Security algorithms: HTTPS | Depth: 46 mm | Wireless isolation: Yes | Virtual LAN features: VLAN mapping | Height: 37.7 mm |

Mounting kit: Yes | Antenna direction type: Omni-directional | Ethernet LAN (RJ-45) ports: 1 | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Wi-Fi Multimedia (WMM)/(WME): Yes | Antenna features: Detachable antenna | Security algorithms: WPA2-PSK | Power over Ethernet (PoE): Yes | Quantity per pack: 1 pc(s) | 6 GHz: No | Antenna gain level (max): 3 dBi | Maximum data transfer rate: 300 Mbit/s | Reset button: Yes | Antenna type: External | 5 GHz: No | Power consumption (typical): 4.11 W | Placement: Pole, Wall | Product colour: White | Warnings: Do not expose to prolonged moisture. | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes