



TP-Link Archer AC1200 Wireless Dual Band 4G LTE Router



Modelis: Archer MR400

Gamintojas: TP-LINK

EAN: 6935364080662

Prekės kodas: 363446

83.99€

Certification: CE, RoHS | Receiver sensitivity: 5GHz: 11a 54M: -74dBm 11ac HT20: -67dBm 11ac HT40: -64dBm 11ac HT80 : -60dBm 11n HT20: -71dBm 11n HT40: -70dBm 2.4G: 11g 54M: -76dBm 11n HT20: -73dBm 11n HT40: -67dBm | VPN support: PPTP, L2TP, IPSec | Warnings: Do not expose the device to water or moisture. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to extreme temperatures. | Wi-Fi standards: 802.11g | Supported network protocols: IPv4, IPv6 | AC adapter included: Yes | Universal Plug and Play (UPnP): Yes | Operating relative humidity (H-H): 10 - 90% | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Width: 174 mm | Windows operating systems supported: Windows 8 | WLAN data transfer rate (max): 867 Mbit/s | VPN tunnels quantity: 10 | Access Control List (ACL): Yes | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows NT | On/off switch: Yes | WAN connection type: RJ-45 | GSM bands supported: 1900 MHz | Output current: 1.5 A | Windows operating systems supported: Windows 8.1 | 3G: Yes | Antennas quantity: 2 | Storage relative humidity (H-H): 5 - 90% | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows XP Professional x64 | Wi-Fi standards: 802.11b | Windows

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

operating systems supported: Windows 10 | 3G/4G USB modem compatibility: No | Ethernet LAN: Yes | 4G: Yes | Output voltage: 12 V | 2G standards: GPRS | Wall mountable: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Linux operating systems supported: Yes | Harmonized System (HS) code: 85176990 | 2G standards: Edge | SIM card slot: Yes | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 4 (802.11n) | Cabling technology: 10/100Base-T(X) | 2G standards: GSM | 4G standard: LTE | Firewall: Yes | Operating temperature (T-T): 0 - 40 °C | Ethernet WAN: Yes | DSL WAN: No | Mac operating systems supported: MacOS | Windows operating systems supported: Windows 2000 | DoS attack prevention: Yes | Windows operating systems supported: Windows 7 | Product type: Tabletop router | Mac compatibility: Yes | Windows operating systems supported: Windows Vista | Height: 33.5 mm | Windows operating systems supported: Windows XP Home x64 | Cables included: LAN (RJ-45) | DHCP server: Yes | GSM bands supported: 850 | DMZ support: Yes | Ethernet LAN interface type: Fast Ethernet | Firewall security: DoS, SPI Firewall, IP and MAC Address Binding | GSM bands supported: 900 | Dynamic DNS (DDNS): Yes | GSM bands supported: 1800 | USB port: No | Package height: 70 mm | Port forwarding: Yes | Depth: 124.5 mm | SIM card type: MicroSIM | Detachable antenna(s): Yes | WPS push button: Yes | 4G bands supported: 2100 | 4G bands supported: 800 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 4G bands supported: 900 | 4G bands supported: 2600 | Quick installation guide: Yes | Package depth: 223 mm | VPN server: PPTP VPN, IPSec VPN, OpenVPN | 4G bands supported: 1800 | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | 3G bands supported: 900 | 3G standards: DC-HSPA+ | 3G bands supported: 2100 | 3G standards: HSPA | Package width: 307 mm | 3G standards: UMTS | Windows operating systems supported: Windows XP Professional | Antenna design: Internal & external | Memory card slot(s): No | Transmit power: CE: 20dBm(2.4GHz), 23dBm(5GHz) | WLAN data transfer rate (second band): 867 Mbit/s | VPN Passthrough: Yes | Guest access: Yes | Mobile network generation: 4G | WLAN data transfer rate (first band): 450 Mbit/s | Product colour: Black | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 3 | Package weight: 670 g | DHCP client: Yes | Stateful Packet Inspection (SPI): Yes | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 10 | Security algorithms: 128-bit WEP | Networking standards: IEEE 802.11b | Package type: Box | Security algorithms: WPA | Networking standards: IEEE 802.11ac | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11a | Web-based management: Yes | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: WPA-PSK | Reset button: Yes | LED indicators: LAN, Power, Status, WLAN | Power source type: DC

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903