TP-Link Archer MR202 wireless router Fast Ethernet Dual-band (2.4 GHz 5 GHz) 4G Black

Modelis: MR202

Gamintojas: TP-LINK

EAN: 8885020625745

Prekės kodas: 363451

64.99€

Certification: CE, RoHS | Receiver sensitivity: 5 GHz: 11a 54M: -78 dBm 11ac VHT20: -92 dBm 11ac VHT20: -72 dBm 11ac VHT40: -90 dBm 11ac VHT40: -67 dBm 11ac VHT80: -87 dBm 11ac VHT80: -64 dBm 2,4 GHz: 11g 54M: -74 dBm 11n HT20: -91 dBm 11n HT20: -72 dBm 11n HT40: -88 dBm 11n HT40: -69 dBm | VPN support: PPTP VPN, OpenVPN | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11ac | DHCP client: Yes | Web-based management: Yes | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | LED indicators: LAN, Power, WAN, WLAN | Stateful Packet Inspection (SPI): Yes | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 100 | DC-in jack: Yes | Reset button: Yes | Product colour: Black | Depth: 124.5 mm | Ethernet LAN: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Windows operating systems supported: Windows 10 | 3G/4G USB modem compatibility: No | 4G bands supported: 700 | 4G bands supported: 2300 | Quality of Service (QoS) support: Yes | 4G bands

supported: 900 | Windows operating systems supported: Windows NT | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 MHz | Quick installation guide: Yes | Product type: Tabletop router | DoS attack prevention: Yes | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | 4G bands supported: 1800 | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | UMTS bands supported: 850 | Mac operating systems supported: Yes | DSL WAN: No | 4G: Yes | Output voltage: 12 V | Windows operating systems supported: Windows XP | UMTS bands supported: 2100 MHz | Mobile network generation: 4G | Windows operating systems supported: Windows 8 | Cables included: LAN (RJ-45) | DHCP server: Yes | Transmit power: 20dBm(2.4G) 23dBm(5G) | Firewall security: IP and MAC Address Binding | Firewall: Yes | Ethernet LAN interface type: Fast Ethernet | Ethernet LAN (RJ-45) ports: 3 | DMZ support: Yes | Port forwarding: Yes | Output current: 1 A | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 | Wi-Fi standards: Wi-Fi 5 (802.11ac) | WLAN data transfer rate (second band): 433 Mbit/s | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | 3G: Yes | Antennas quantity: 2 | Wi-Fi standards: 802.11a | Plug and Play: Yes | WLAN data transfer rate (max): 733 Mbit/s | Security algorithms: 128-bit WEP | UMTS bands supported: 900 | WLAN data transfer rate (first band): 300 Mbit/s | Width: 174 mm | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA | 3G standards: UMTS | 4G standard: LTE-TDD & LTE-FDD | Operating relative humidity (H-H): 10 - 90% | Cabling technology: 10/100Base-T(X) | Wi-Fi standards: 802.11g | Guest access: Yes | Windows operating systems supported: Windows 7 | Universal Plug and Play (UPnP): Yes | Static IP: Yes | Height: 33.5 mm | Antenna design: External | Security algorithms: WPA2-PSK | Wi-Fi standards: Wi-Fi 4 (802.11n) | Memory card slot(s): No | Security algorithms: WPA | Windows operating systems supported: Windows 98SE | Operating temperature (T-T): 0 - 40 °C | 4G bands supported: 2100 | 4G bands supported: 800 | USB port: No | Dynamic DNS (DDNS): Yes | Port triggering: Yes | Ethernet WAN: Yes | WAN connection type: RJ-45 | Windows operating systems supported: Windows 2000 | Power source type: DC | Linux operating systems supported: Yes | Point-to-point protocol over Ethernet (PPPoE): Yes | Wi-Fi standards: 802.11b | Dynamic IP: Yes | SIM card slot: Yes | Supported network protocols: IPv4, IPv6 | Number of Ethernet LAN/WAN ports: 1 | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not expose the device to water or moisture.