



TP-Link Omada Gigabit VPN Router



Modelis: TL-ER605

Gamintojas: TP-LINK

EAN: 6935364089597

Prekės kodas: 363464

68.99€

Supported protocols: IPsec/PPTP/L2TP | Certification: CE, FCC, RoHS | NAT functionality: • One-to-One NAT • Multi-Net NAT • Virtual Server • Port Triggering • NAT-DMZ • FTP/H.323/SIP/IPSec/PPTP ALG, UPnP | VPN support: • 20 IPsec VPN Tunnels • LAN-to-LAN, Client-to-LAN • Main, Aggressive Negotiation Mode • DES, 3DES, AES128, AES192, AES256 Encryption Algorithm • IKEv1/v2 • MD5, SHA1 Authentication Algorithm • NAT Traversal (NAT-T) • Dead Peer Detection (DPD) • Perfect Forward Secrecy (PFS) • PPTP VPN Server • 10 PPTP VPN Clients • 16 Tunnels • PPTP with MPPE Encryption • L2TP VPN Server • 10 L2TP VPN Clients • 16 Tunnels • L2TP over IPsec • OpenVPN Server • 10 OpenVPN Clients • 16 OpenVPN Tunnels | Network address translation (NAT): Yes | Reset button: Yes | Networking standards: IEEE 802.3u | Security algorithms: 256-bit AES | Product colour: Black | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Storage temperature (T-T): -40 - 70 °C | LED indicators: USB | Ethernet LAN data rates: 10 | Rack capacity: 1U | LED indicators: LAN | AC input frequency: 50 - 60 Hz | LED indicators: WAN | Windows operating systems supported: Windows XP | Windows operating systems supported: Windows 8 | Operating relative humidity (H-H): 10 - 90% | Security algorithms: 192-bit AES | Ethernet LAN data rates: 100 Mbit/s | Windows operating systems supported: Windows 98SE | Quick start guide: Yes | Package

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

width: 190 mm | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Package weight: 650 g | DHCP client: Yes | Security algorithms: 128-bit AES | Windows operating systems supported: Windows 10 | Ethernet LAN data rates: 1000 Mbit/s | Power source type: AC | Security algorithms: 3DES | Security algorithms: MD5 | Ethernet LAN (RJ-45) ports: 5 | Windows operating systems supported: Windows 2000 | Operating temperature (T-T): 0 - 40 °C | Internal memory type: DRAM | LED indicators: System | AC input voltage: 120 - 240 V | Storage relative humidity (H-H): 5 - 90% | Security algorithms: SHA-1 | Windows operating systems supported: Windows NT | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | LED indicators: Activity | Windows operating systems supported: Windows 7 | Web-based management: Yes | Security algorithms: DES | Ethernet interface type: Gigabit Ethernet | Routing protocols: RIP-1 | Manual: Yes | Traffic control: Yes | DSL WAN: No | USB ports quantity: 1 | Cables included: AC | 3G/4G USB modem compatibility: No | Internal memory: 256 MB | Depth: 101 mm | Supported network protocols: TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP, HTTP, DNS, IPsec, PPTP, L2TP | Authentication method: SHA-1, MD5 | Embedded DRAM (eDRAM) memory: 128 MB | Power consumption (typical): 7.94 W | Universal Plug and Play (UPnP): Yes | Ethernet WAN: Yes | System event log: Yes | DoS attack prevention: Yes | VPN tunnels quantity: 20 | Routing protocols: RIP-2 | URL filtering: Yes | Mac operating systems supported: MacOS | Concurrent connections: 150000 | Package depth: 254 mm | SIM card slot: No | Quick installation guide: Yes | Rack mounting: Yes | Width: 158 mm | Height: 25 mm | Linux operating systems supported: Yes | Firewall: Yes | Policy-based routing: Yes | Flash memory: 128 MB | VLAN support: Yes | DHCP server: Yes | ARP attack prevention: Yes | Flash memory: 16 MB | Management protocols: Telnet | Package height: 60 mm | Cabling technology: 10/100/1000Base-T(X) | Warnings: Do not open the appliance housing - risk of electric shock. | Warnings: Avoid contact with liquids as this may cause electric shock. | DMZ support: Yes | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Compliance certificates: RoHS

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903