TP-Link AX1500 Whole Home Mesh Wi-Fi 6 System

Modelis: Deco X10(1-pack)

Gamintojas: TP-LINK

EAN: 4895252503197

Prekės kodas: 363481

53.99€

WLAN data transfer rate (second band): 1201 Mbit/s | Number of guest networks (2.4 GHz): 1 | BeamForming: Yes | IGMP proxy: Yes | Tagged VLAN: Yes | WLAN data transfer rate (first band): 300 Mbit/s | Apps supported: TP-Link Deco | Dynamic IP: Yes | Number of guest networks (5 GHz): 1 | MU-MIMO technology: Yes | Guest access: Yes | Maximum coverage: 190 m² | Number of units included: 1 pc(s) | Warnings: Do not open the appliance housing - risk of electric shock. | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Avoid contact with liquids as this may cause electric shock. | Product type: Mesh router | DHCP server: Yes | Height: 114 mm | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11ax | Networking standards: IEEE 802.11a | Operating modes: Router Mode, Access Point Mode | IGMP snooping: Yes | Ethernet cable: Yes | Operating relative humidity (H-H): 10 - 90% | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Dynamic DNS (DDNS): Yes | Ethernet LAN (RJ-45) ports: 2 | Wi-Fi standards: 802.11g | Wi-Fi standards: Wi-Fi 4 (802.11n) | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Width: 110 mm | Port

forwarding: Yes | DHCP client: Yes | Wi-Fi standards: 802.11b | Parental control: Yes | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Security algorithms: WPA2 | LED indicators: Yes | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | MIMO: Yes | Quality of Service (QoS) support: Yes | Depth: 110 mm | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Antenna type: Internal | Universal Plug and Play (UPnP): Yes | Static IP: Yes | WLAN data transfer rate (max): 1500 Mbit/s | Product colour: White | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | Security algorithms: WPA