



## TP-Link 8-Port Gigabit Easy Smart Switch



Modelis: TL-SG108E

Gamintojas: TP-LINK

EAN: 6935364021856

Prekės kodas: 363489

# 30.99€

Certification: FCC, CE, RoHS | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Input voltage: 9 V | Link aggregation: Yes | Package width: 130 mm | Switch layer: L2 | VLAN support: Yes | Input current: 0.6 A | Operating temperature (T-T): 0 - 40 °C | Cables included: AC | Security algorithms: SNMP | Jumbo frames: 15000 | Loop protection: Yes | LED indicators: Yes | Networking standards: IEEE 802.1ab | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Security algorithms: SNMPv2 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package depth: 191 mm | Storage relative humidity (H-H): 5 - 90% | Package weight: 630 g | Number of VLANs: 32 | Power consumption (max): 3.55 W | Auto-negotiation: Yes | Package height: 92 mm | Operating relative humidity (H-H): 10 - 90% | Virtual LAN features: Port-based VLAN | Gigabit Ethernet (copper) ports quantity: 8 | Plug and Play: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.1p | Switching capacity: 16 Gbit/s | Package type: Box | Power supply included: Yes | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Basic switching RJ-45 Ethernet ports quantity: 8 | MAC address table: 4000 entries | Height: 25 mm | Product colour: Black | Housing material: Metal | Port mirroring: Yes | Width: 158 mm | User guide: Yes | Heat dissipation: 12.12 BTU/h | Switch type: Managed |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

Forwarding rate: 11.9 Mpps | Cable types supported: Cat5 | Cable types supported: Cat5e | Auto MDI/MDI-X: Yes | Packet buffer memory: 1.5 MB | Web-based management: Yes | Depth: 101 mm | 10G support: No | Broadcast storm control: Yes | Cable types supported: Cat4 | IGMP snooping: Yes | Cable types supported: Cat3 | Jumbo frames support: Yes | Store-and-forward: Yes | Power source: DC

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903