



TP-Link 16-Port Gigabit Easy Smart Switch with 8-Port PoE+



Modelis: TL-SG1016PE

Gamintojas: TP-LINK

EAN: 6935364098865

Prekės kodas: 363492

138.99€

Compatible operating systems: Windows | User guide: Yes | Product colour: Black | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 10G support: No | Package depth: 400 mm | Package type: Box | Package height: 80 mm | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 10BASE-T | Rack mounting: Yes | Copper ethernet cabling technology: 1000BASE-T | Power source: AC/PoE | VLAN support: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Web-based management: Yes | Packet buffer memory: 4.1 MB | Port mirroring: Yes | Auto MDI/MDI-X: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes | Operating relative humidity (H-H): 10 - 90% | AC input frequency: 50/60 Hz | Power over Ethernet (PoE): Yes | Power supply included: Yes | Compliance certificates: Federal Communications Commission (FCC) | Switching capacity: 32 Gbit/s | Compliance certificates: RoHS | Compliance certificates: CE | Power connector: AC-in jack | Number of VLANs: 4000 | Operating temperature (T-

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

T): 0 - 40 °C | Networking standards: IEEE 802.3i | Width: 294 mm | IGMP snooping: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Housing material: Metal | Store-and-forward: Yes | Networking standards: IEEE 802.3u | Resource CD: Yes | Total Power over Ethernet (PoE) budget: 110 W | Number of fans: 1 fan(s) | Jumbo frames support: Yes | Storage relative humidity (H-H): 5 - 90% | Switch layer: L2 | Height: 44 mm | Package weight: 2.28 kg | Basic switching RJ-45 Ethernet ports quantity: 16 | Cables included: AC | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Form factor: 1U | Warnings: Do not open the case or try to repair it yourself. | Depth: 180 mm | Stackable: No | Flow control support: Yes | Broadcast storm control: Yes | Power consumption (max): 124.4 W | Power over Ethernet plus (PoE+) ports quantity: 8 | LED indicators: Yes | AC input voltage: 100 - 240 V | Package width: 250 mm | Warnings: Ensure the unit is adequately ventilated during operation. | Switch type: Managed | Sustainability compliance: Yes | Forwarding rate: 23.8 Mpps | Gigabit Ethernet (copper) ports quantity: 16 | Cable types supported: Cat3 | Maximum cable length: 100 m | Rack mount kit: Yes | Jumbo frames: 10000 | Link aggregation: Yes | Virtual LAN features: Port-based VLAN | Virtual LAN features: Tagged VLAN | Cable types supported: Cat4 | Cable types supported: Cat6 | Cable types supported: Cat5 | Cable types supported: Cat5e | Number of queues: 4

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903