



# TP-Link 18-Port Gigabit Rackmount Switch with 16 PoE+



Modelis: TL-SG1218MP

Gamintojas: TP-LINK

EAN: 6935364072155

Prekės kodas: 363503

## 201.99€

Certification: CE, FCC, RoHS | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package depth: 528 mm | Product colour: Black | Packet buffer memory: 4.1 MB | Ethernet LAN data rates: 10,100,1000 Mbit/s | Auto MDI/MDI-X: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes | Form factor: 1U | Package width: 250 mm | Networking standards: IEEE 802.3u | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Operating relative humidity (H-H): 10 - 90% | Flow control support: Yes | Total Power over Ethernet (PoE) budget: 250 W | Combo SFP ports quantity: 2 | AC input voltage: 100 - 240 V | Switch type: Unmanaged | LED indicators: Yes | Package height: 80 mm | Power consumption (max): 286.64 W | Power over Ethernet plus (PoE+) ports quantity: 16 | Package weight: 3.05 kg | Cables included: AC | Switching capacity: 36 Gbit/s | Full duplex: Yes | Basic switching RJ-45 Ethernet ports quantity: 18 | Power source: AC | Heat dissipation: 977.44 BTU/h | Height: 44 mm | Width: 440 mm | Networking

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Power over Ethernet (PoE): Yes | Jumbo frames support: Yes | 10G support: No | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Housing material: Metal | AC input frequency: 50 - 60 Hz | Operating temperature (T-T): 0 - 50 °C | Power supply included: Yes | Depth: 180 mm | Harmonized System (HS) code: 85176990 | Quick start guide: Yes | Rack mounting: Yes | Number of fans: 2 fan(s) | Cable types supported: Cat4 | MAC address auto-aging supported: Yes | Forwarding rate: 26.78 Mpps | Half duplex: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Jumbo frames: 10000 | Traffic classification: Yes | Cable types supported: Cat6 | Cable types supported: Cat3 | Gigabit Ethernet (copper) ports quantity: 18 | Warnings: Ensure the unit is adequately ventilated during operation. | MAC address auto-learning supported: Yes | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Do not open the case or try to repair it yourself.