



TP-Link Omada 24-Port Gigabit L2+ Managed Switch with 4 SFP Slots



Modelis: TL-SG3428

Gamintojas: TP-LINK

EAN: 6935364010713

Prekės kodas: 363508

183.99€

ARP inspection: Yes | Policy-based routing: Yes | Number of static routes: 48 | Access Control List (ACL): Yes | IP routing: Yes | MAC address table: 16000 entries | Heat dissipation: 70.3 BTU/h | Loop protection: Yes | IPv4 & IPv6 features: IPv6 Telnet | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Port mirroring: Yes | IPv4 & IPv6 features: IPv6 ping | IPv4 & IPv6 features: IPv4/IPv6 access-control list (ACL) | Management protocols: SNMPv1/v2c/v3, SNTP | Static port security: Yes | GARP VLAN Registration Protocol (GVRP): Yes | SFP module slots quantity: 4 | Packet buffer memory: 12 MB | Rate limiting: Yes | IPv4 & IPv6 features: IPv6 tracer | Number of VLANs: 4000 | Console port: RJ-45/micro-USB | Cloud-managed: Yes | IGMP snooping: Yes | Configuring Location Settings (CLI): Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Switch type: Managed | Spanning tree protocol: Yes | Jumbo frames: 9000 | LED indicators: Yes | DHCP features: DHCP snooping | DHCP features: DHCP server | 10G support: No | Form factor: 1U | Authentication: MAC-based authentication, Port-based authentication | Switch layer: L2/L3 | BPDU

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

filtering/protection: Yes | Jumbo frames support: Yes | Forwarding rate: 41.66 Mpps | DHCP features: DHCPv6 snooping | System event log: Yes | Flow control support: Yes | DHCP features: DHCPv6 client | DHCP features: DHCP client | DHCP features: DHCP relay | IP-MAC-Port binding: Yes | Power over Ethernet (PoE): No | Link aggregation: Yes | Store-and-forward: Yes | Multicast support: Yes | Virtual LAN features: Voice VLAN | Virtual LAN features: Private VLAN | Virtual LAN features: Tagged VLAN | Operating temperature (T-T): 0 - 45 °C | Head-of-line (HOL) blocking: Yes | AC input voltage: 100 - 240 V | Gigabit Ethernet (copper) ports quantity: 24 | IPv4 routes: 48 | AC input frequency: 50/60 Hz | Authentication type: AAA, RADIUS, TACACS+ | Networking standards: IEEE 802.3ab | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.3i | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.3z | Storage relative humidity (H-H): 5 - 90% | MIB support: Yes | Networking standards: IEEE 802.3u | Power consumption (max): 20.6 W | Quick start guide: Yes | IPv6 routes: 48 | Virtual LAN features: Protocol-based VLAN | SSH/SSL support: Yes | Static route: Yes | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | Cables included: LAN (RJ-45) | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Product colour: Black | VLAN support: Yes | Rack mounting: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Height: 44 mm | Width: 440 mm | Power supply included: No | Depth: 180 mm | Switching capacity: 56 Gbit/s | Power source: AC

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903