



TP-Link Omada 48-Port Gigabit L2+ Managed Switch with 4 10GE SFP+ Slots

Modelis: TL-SG3452X

Gamintojas: TP-LINK

EAN: 6935364006471

Prekės kodas: 363512

453.99€

Certification: CE, FCC, RoHS | Head-of-line (HOL) blocking: Yes | BPDU filtering/protection: Yes | ARP inspection: Yes | Authentication type: AAA, RADIUS, TACACS+ | IPv4 & IPv6 features: IPv6 ping | IPv4 & IPv6 features: IPv4/IPv6 access-control list (ACL) | IPv4 & IPv6 features: IPv6 Telnet | IPv4 & IPv6 features: IPv6 traceroute | IP-MAC-Port binding: Yes | GARP VLAN Registration Protocol (GVRP): Yes | Cloud-managed: Yes | IPv4 routes: 48 | IPv6 routes: 48 | Number of static routes: 48 | Configuring Location Settings (CLI): Yes | Basic switching RJ-45 Ethernet ports quantity: 48 | Virtual LAN features: Voice VLAN | Queue scheduling algorithms: WRR+SP | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Ensure the unit is adequately ventilated during operation. | Virtual LAN features: Private VLAN | Virtual LAN features: VLAN mapping | Link aggregation: Yes | Rack rails: Yes | VLAN support: Yes | Multicast support: Yes | Virtual LAN features: Tagged VLAN | Width: 440 mm | Rack mounting: Yes | IGMP snooping: Yes | Port mirroring: Yes | 10G

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

support: Yes | Authentication: Auto VLAN, Guest VLAN, MAC-based authentication, Port-based authentication | Number of VLANs: 4000 | Rack mount kit: Yes | Queue scheduling algorithms: SP | Password protection: Yes | Warnings: Do not open the case or try to repair it yourself. | SSH/SSL support: Yes | Number of fans: 0 fan(s) | Spanning tree protocol: Yes | Jumbo frames: 9000 | Jumbo frames support: Yes | Rate limiting: Yes | IGMP proxy: Yes | Height: 44 mm | MAC address table: 16000 entries | Packet buffer memory: 12 MB | Console port: RJ-45/micro-USB | Switch type: Managed | Heat dissipation: 111.65 BTU/h | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | MIB support: RFC1213, RFC2233, RFC1643, RFC1493, RFC2674, RFC2819, RFC2021, RFC2620, RFC2618, | Power connector: AC-in jack | Loop protection: Yes | Huawei-proprietary MIB: Y | Public MIB: Y | DHCP features: DHCP server | Switch layer: L2+ | Forwarding rate: 130.9 Mpps | System event log: Yes | DHCP features: DHCP client | DHCP features: DHCP relay | Depth: 220 mm | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | Static route: Yes | Power supply included: Yes | Switching capacity: 176 Gbit/s | Management protocols: SNMPv1/v2c/v3, SNTP | Static port security: Yes | Operating relative humidity (H-H): 10 - 90% | Package type: Box | Power over Ethernet (PoE): No | Cables included: AC | LED indicators: Yes | AC input voltage: 100 - 240 V | Power source: AC | Product colour: Black | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Quick start guide: Yes | Power consumption (max): 32.72 W | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Form factor: 1U | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.1D | Operating temperature (T-T): 0 - 45 °C | Storage relative humidity (H-H): 5 - 90% | AC input frequency: 50/60 Hz

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903