



# TP-Link JetStream 48- Port Gigabit and 4-Port 10GE SFP+ L2+ Managed Switch with 48-Port PoE+

Modelis: TL-SG3452XP

Gamintojas: TP-LINK

EAN: 6935364006495

Prekės kodas: 363513

---

## 748.99€

---

Certification: CE, FCC, RoHS | Rack mounting: Yes | Harmonized System (HS) code: 85176990 | Power over Ethernet (PoE): Yes | IGMP snooping: Yes | Width: 440 mm | Rack rails: Yes | Quick start guide: Yes | Switching capacity: 176 Gbit/s | Basic switching RJ-45 Ethernet ports quantity: 48 | VLAN support: Yes | AC input voltage: 100 - 240 V | Form factor: 1U | Operating temperature (T-T): 0 - 40 °C | Configuring Location Settings (CLI): Yes | Forwarding rate: 130.9 Mpps | MAC address table: 16000 entries | Switch layer: L2+ | Power supply included: Yes | Multicast support: Yes | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | DHCP features: DHCP client | DHCP features: DHCP relay | System event log: Yes | DHCP features: DHCP server | ARP inspection: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

BPDU filtering/protection: Yes | Depth: 330 mm | Power over Ethernet (PoE) ports quantity: 48 | AC input frequency: 50 - 60 Hz | Operating relative humidity (H-H): 10 - 90% | Port mirroring: Yes | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.1Q | Rate limiting: Yes | Web-based management: Yes | MAC address filtering: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Height: 44 mm | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3ae | Power source: AC | Console port: RJ-45/micro-USB | Cloud-managed: Yes | Networking standards: IEEE 802.3af | IP-MAC-Port binding: Yes | Heat dissipation: 2169.2 BTU/h | Switch type: Managed | Static port security: Yes | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1w | Number of fans: 3 fan(s) | Networking standards: IEEE 802.3u | Jumbo frames support: Yes | Spanning tree protocol: Yes | Storage relative humidity (H-H): 5 - 90% | Jumbo frames: 9216 | Broadcast storm control: Yes | Cables included: AC | Link aggregation: Yes | Store-and-forward: Yes | Flash memory: 32 MB | Head-of-line (HOL) blocking: Yes | Total Power over Ethernet (PoE) budget: 500 W | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Authentication: Auto VLAN, Guest VLAN | 10G support: Yes | Flow control support: Yes | SSH/SSL support: Yes | Internal memory: 512 MB | Product colour: Black

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903