



TP-Link LiteWave 5-Port Gigabit Desktop Switch with 4- Port PoE+



Modelis: LS105GP

Gamintojas: TP-LINK

EAN: 4895252504545

Prekės kodas: 363515

30.99€

Certification: CE, FCC, RoHS | Auto-negotiation: Yes | Cable types supported: Cat3 | MAC address table: 2000 entries | Warnings: Do not open the case or try to repair it yourself. | Package type: Box | Cable types supported: Cat4 | Basic switching RJ-45 Ethernet ports quantity: 5 | Networking standards: IEEE 802.3x | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3u | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3af | Warnings: Ensure the unit is adequately ventilated during operation. | Switching capacity: 10 Gbit/s | Operating relative humidity (H-H): 10 - 90% | Auto MDI/MDI-X: Yes | MAC address auto-aging supported: Yes | Height: 25 mm | Power source: DC/PoE | Cable types supported: Cat5 | Cable types supported: Cat5e | DC input voltage: 53.5 V | AC input voltage: 220 V | Operating temperature (T-T): 0 - 40 °C | LED indicators: Yes | Total Power over Ethernet (PoE) budget: 65 W | Heat dissipation: 253.16 BTU/h | Depth: 98 mm | Power over Ethernet (PoE) ports

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

quantity: 4 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Power consumption (max): 74.46 W | Switch type: Unmanaged | Jumbo frames: 16000 | Width: 99.8 mm | Power supply included: Yes | AC input frequency: 50 Hz | MAC address auto-learning supported: Yes | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Store-and-forward: Yes | Forwarding rate: 7.44 Mpps | Networking standards: IEEE 802.3i | 10G support: No | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | User guide: Yes | Flow control support: Yes | IGMP snooping: Yes | Power over Ethernet (PoE): Yes | Product colour: Black

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903