



TP-Link LiteWave 10- Port Gigabit Desktop Switch with 8-Port PoE+



Modelis: LS1210GP

Gamintojas: TP-LINK

EAN: 4895252504569

Prekės kodas: 363517

59.99€

Certification: CE, FCC, RoHS | LED indicators: Yes | AC input voltage: 220 V | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3u | AC input frequency: 50 Hz | Networking standards: IEEE 802.3af | Product colour: Black | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 5 - 90% | Basic switching RJ-45 Ethernet ports quantity: 9 | Package type: Box | Power source: DC/PoE | Power supply included: Yes | Power consumption (max): 76.96 W | Operating relative humidity (H-H): 10 - 90% | MAC address table: 4000 entries | Power over Ethernet (PoE) ports quantity: 8 | Height: 26 mm | Width: 209 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 10G support: No | Power over Ethernet (PoE): Yes | User guide: Yes | Operating temperature (T-T): 0 -

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

40 °C | Switching capacity: 20 Gbit/s | Total Power over Ethernet (PoE) budget: 61 W | Auto MDI/MDI-X: Yes | SFP module slots quantity: 1 | Depth: 126 mm | Switch type: Unmanaged | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Do not open the case or try to repair it yourself. | Heat dissipation: 261.66 BTU/h | Warnings: Ensure the unit is adequately ventilated during operation. | DC input voltage: 53.5 V | Forwarding rate: 14.88 Mpps | Jumbo frames: 16000 | Flow control support: Yes | Store-and-forward: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Auto-negotiation: Yes | Cable types supported: Cat4 | Cable types supported: Cat3

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903