



TP-Link Omada 10-Port Gigabit Easy Managed Switch with 8- Port PoE+



Modelis: ES210GMP

Gamintojas: TP-LINK

EAN: 8885020620955

Prekės kodas: 363520

126.99€

Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Width: 209 mm | Power over Ethernet (PoE): Yes | Package type: Box | Basic switching RJ-45 Ethernet ports quantity: 10 | IGMP snooping: Yes | Auto MDI/MDI-X: Yes | VLAN support: Yes | Operating relative humidity (H-H): 10 - 90% | Link aggregation: Yes | DHCP features: DHCP client | Jumbo frames support: Yes | Wall mountable: Yes | Reset button: Yes | Switch type: Managed | Power source: DC | Combo SFP ports quantity: 1 | Fanless: Yes | Input current: 2.43 A | Power supply included: Yes | Jumbo frames: 15 | Cables included: AC | Store-and-forward: Yes | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.1ab | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3af | Depth: 126 mm | Virtual LAN features: MTU VLAN | Virtual LAN features: Port-based VLAN | Forwarding rate: 14.88 Mpps | Height: 26 mm | Switching capacity: 20 Gbit/s | Power over Ethernet plus (PoE+) ports quantity: 8 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Flow control support: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | User guide: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | 10G support: No | Virtual LAN features: Tagged VLAN | Storage relative humidity (H-H): 5 - 90% | Cloud-managed: Yes | Transmission distance (max): 0.25 km | DC input voltage: 53.5 V | Packet buffer memory: 4 MB | Operating temperature (T-T): 0 - 40 °C | Port mirroring: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes | Total Power over Ethernet (PoE) budget: 123 W | Product colour: Black