# TP-Link JetStream 8-Port Gigabit Smart Switch

Modelis: SG2008

Gamintojas: TP-LINK

EAN: 6935364010546

Prekės kodas: 363521

## 89.00€

Certification: CE, FCC, RoHS | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3u | Product colour: Black | Web-based management: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power over Ethernet (PoE): No | Operating temperature (T-T): 0 - 40 °C | Width: 209 mm | Input voltage: 12 V | Height: 26 mm | Cables included: AC | Harmonized System (HS) code: 85176990 | Internal memory: 256 MB | Storage relative humidity (H-H): 5 - 90% | Power supply included: Yes | Jumbo frames support: Yes | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Operating relative humidity (H-H): 10 - 90% | Security algorithms: SSH | Networking standards: IEEE 802.3i | 10G support: No | User guide: Yes | Switching capacity: 16 Gbit/s | Power connector: DC-in jack | Power consumption (max): 6.42 W | Wall mountable: Yes | Depth: 126 mm | VLAN support: Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-TX | Basic switching RJ-45 Ethernet ports quantity: 8 | Flash memory: 32 MB | Copper ethernet cabling technology: 1000BASE-T | Security

algorithms: SSH-2 | LED indicators: Yes | Power source: DC | Input current: 1 A | DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCPv6 snooping | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat4 | Cable types supported: Cat3 | Rate limiting: Yes | Store-and-forward: Yes | Gigabit Ethernet (copper) ports quantity: 8 | Broadcast storm control: Yes | Link aggregation: Yes | Switch layer: L2/L2+ | System event log: Yes | DHCP features: DHCP server | Virtual LAN features: MAC address-based VLAN | BPDU filtering/protection: Yes | DHCP features: DHCP snooping | Virtual LAN features: Protocol-based VLAN | MIB support: Y | Multicast support: Yes | Management protocols: SNMPv1/v2c/v3, SNTP | Virtual LAN features: Tagged VLAN | DHCP features: DHCPv6 client | MAC address table: 8000 entries | Virtual LAN features: Voice VLAN | Number of VLANs: 4000 | Forwarding rate: 11.9 Mpps | SSH/SSL support: Yes | Static route: Yes | Flow control support: Yes | Number of static routes: 32 | Fanless: Yes | ARP inspection: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | GARP VLAN Registration Protocol (GVRP): Yes | Port mirroring: Yes | Cloud-managed: Yes | IGMP snooping: Yes | IP-MAC-Port binding: Yes | Switch type: Managed | Number of IP interfaces: 16 | Access Control List (ACL): Yes