



TP-Link Omada ES220GMP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Modelis: ES220GMP

Gamintojas: TP-LINK

EAN: 8885020625943

Prekės kodas: 363522

215.99€

Zero Touch Provisioning (ZTP): Yes | Unified static configuration: Yes | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3u | Power consumption (max): 289.7 W | Switching capacity: 40 Gbit/s | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Web-based management: Yes | Networking standards: IEEE 802.3z | Operating temperature (T-T): -5 - 50 °C | Total Power over Ethernet (PoE) budget: 250 W | Networking standards: IEEE 802.1ab | Power over Ethernet (PoE) power per port: 30 W | Flash

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

memory: 64 MB | Mean time between failures (MTBF): 310550.7 h | Height: 44 mm | Cables included: AC | VLAN support: Yes | Depth: 180 mm | LED indicators: Yes | Package type: Box | Surge protection: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | User guide: Yes | Product colour: Black | Power source: AC | Storage relative humidity (H-H): 5 - 90% | AC input voltage: 100 - 240 V | Networking standards: IEEE 802.3i | Noise level: 41.5 dB | Firmware upgradeable: Yes | Auto MDI/MDI-X: Yes | Jumbo frames support: Yes | Power supply included: Yes | Operating relative humidity (H-H): 10 - 90% | Number of fans: 2 fan(s) | AC input frequency: 50/60 Hz | Power over Ethernet (PoE): Yes | SFP module slots quantity: 2 | Width: 440 mm | Rack mounting: Yes | Port mirroring: Yes | Packet buffer memory: 4 MB | Jumbo frames: 15000 | Cloud-managed: Yes | Virtual LAN features: Port-based VLAN | Store-and-forward: Yes | Switch layer: L2 | MAC address table: 8000 entries | Auto-negotiation: Yes | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 16 | Virtual LAN features: MTU VLAN | Stackable: No | Virtual LAN features: Tagged VLAN | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | DHCP features: DHCP client | Link aggregation: Yes | Surge protection voltage: 6 kV | Gigabit Ethernet (copper) ports quantity: 18 | Rack mount kit: Yes | Basic switching RJ-45 Ethernet ports quantity: 18 | Forwarding rate: 29.76 Mpps | Loop protection: Yes | 10G support: No | Power over Ethernet (PoE) type supported: PoE+ | Switch type: Managed | Number of VLANs: 32 | Heat dissipation: 984.88 BTU/h | IGMP snooping: Yes | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Compliance certificates: Federal Communications Commission (FCC) | Fast leave: Yes | Compliance certificates: RoHS | Compliance certificates: CE

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903