



TP-Link Omada ES206GP network switch Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Modelis: ES206GP

Gamintojas: TP-LINK

EAN: 1210002600644

Prekės kodas: 363523

60.98€

Web-based management: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | LED indicators: Yes | Wall mountable: Yes | Switching capacity: 12 Gbit/s | Power over Ethernet plus (PoE+) ports quantity: 4 | Networking standards: IEEE 802.3at | Forwarding rate: 7.4 Mpps | Loop protection: Yes | Input current: 1.31 A | Switch type: Managed | Power source: DC | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.1p | 10G support: No | AC adapter included: Yes | Storage relative humidity (H-

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

H): 5 - 90% | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Networking standards: IEEE 802.1ab | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | User guide: Yes | VLAN support: Yes | Width: 158 mm | Port mirroring: Yes | Basic switching RJ-45 Ethernet ports quantity: 6 | Cloud-managed: Yes | DC input voltage: 53.5 V | Operating temperature (T-T): -5 - 40 °C | Package type: Box | Link aggregation: Yes | Virtual LAN features: Port-based VLAN | Product colour: Black | Virtual LAN features: Tagged VLAN | Depth: 101 mm | Virtual LAN features: MTU VLAN | Transmission distance (max): 0.25 km | MAC address table: 8000 entries | Auto-negotiation: Yes | Auto MDI/MDI-X: Yes | Packet buffer memory: 4 MB | Jumbo frames: 15 | Surge protection: Yes | Gigabit Ethernet (copper) ports quantity: 6 | Jumbo frames support: Yes | Store-and-forward: Yes | Total Power over Ethernet (PoE) budget: 65 W | Surge protection voltage: 6 kV | Height: 25 mm | IGMP snooping: Yes | Reset button: Yes | DHCP features: DHCP client | Power over Ethernet (PoE): Yes | Firmware upgradeable: Yes | Operating relative humidity (H-H): 10 - 90% | Power supply included: Yes | Power over Ethernet (PoE) type supported: PoE+ | Fanless: Yes | Fast leave: Yes | Zero Touch Provisioning (ZTP): Yes | Unified static configuration: Yes | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903