

AG Neovo QM-4302 Digital signage flat panel 108 cm (42.5") IPS 400 cd/m² 4K Ultra HD Black 24/7

Gamintojas: **AG NEOVO** · Modelis: **QM-4302** · EAN: **4710739597035** · Prekės kodas: **364161**



599,91 €

Kaina su PVM

Be PVM: **495,79 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4K UHD 3840 x 2160 resolution
- ✓ 400 nits brightness for indoor public use
- ✓ Built-in USB media playback signage content delivery
- ✓ Flexible display orientation: Landscape/Portrait
- ✓ Rigorous screening of the components for mission-critical 24/7 applications



Aprašymas

QM-4302

The new QM-4302 43-inch 4K digital signage display is designed for digital signage applications that require crisper and clearer image presentation. Featuring a premium IPS panel for 24/7 operation, 4K UHD resolution with a wide viewing angle, and easy-to-use media playback via a USB drive. The QM-4302 digital signage display is ideally used for retail stores, corporate meeting areas, hotels and other public spaces.

EXPERIENCE THE 4K DIFFERENCE

Don't miss a single detail with the powerful 4K digital signage display. View smooth 4K video and images to the new level of detail and clarity. Offering 8.3 million pixels, the QM-4302 provides the ultimate 4K digital signage experience, delivering business messaging, and boost customer engagement.

EMBEDDED IMAGE ENHANCER

The embedded image enhancer features a 3D Deinterlace and Noise Reduction to solve image issues – offering crystal clarity to the most demanding environments.

BLACK-LEVEL ALIGNMENT

Black-level setting- easily adjust the level of brightness from the dark area of the images by remote control.

SIMPLE CONTENT PLAYBACK AND SCHEDULING

The embedded media player allows users to conveniently play content from a USB drive or micro SD card. Simply create scheduled playlists based on time and day and configure playback settings with the included remote control to display your personalised content.

PATENTED ANTI-BURN-IN™ TECHNOLOGY

To combat the effects of traditional LCD burn-in or ghosting, AG Neovo utilises its patented Anti-Burn-in™ Technology to prevent image burn-in and assure the extended life span for displays.

FREE PID COMMAND & CTRL SOFTWARE

PID Command & Ctrl provides intuitive user interfaces for remote management via laptops and mobile devices and offers easy creation on video wall displays. The software also has simple colour calibration, temperature check, IR/key locking options, and time on usage monitoring for daily maintenance.

Techninė specifikacija

Specifications	
Sandėlio grupė	IT > Audiovisual systems > LFD large monitors [+0][-0]
Display	
Display diagonal	108 cm (42.5")
Display technology	IPS
Display resolution	3840 x 2160 pixels
Display brightness	400 cd/m²
HD type	4K Ultra HD
Touchscreen	No
Panel type	IPS
Native aspect ratio	16:9
Response time	5 ms
Contrast ratio (typical)	4500:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Pixel pitch	0.245 x 0.245 mm
Display diagonal (metric)	108 cm
Horizontal scan range	15 - 136 kHz
Vertical scan range	23 - 76 Hz

Haze rate	1%
Surface hardness	3H
Ports & interfaces	
HDMI ports quantity	3
DVI port	No
USB port	Yes
HDMI version	2
VGA (D-Sub) input ports	1
USB ports quantity	1
USB version	2
Ethernet LAN (RJ-45) ports	1
PC Audio in	Yes
RS-232 interface	Yes
Remote (IR) output	1
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal
Panel mounting interface	200 x 200 mm
Anti-glare screen	Yes
Mounting type	Wall
Performance	
Purpose	Universal
Operating hours (hours/days)	24/7
Power	
Power consumption (typical)	102 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W

Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	102 kWh
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G
Computer system	
Computer system	No
Built-in processor	No
Weight & dimensions	
Display width	973 mm
Display depth	63.5 mm
Display height	561.2 mm
Display weight	10.8 kg
Packaging data	
Package width	1070 mm
Package depth	141 mm
Package height	673 mm
Package weight	13.6 kg
Packaging content	
Remote control included	Yes
Batteries included	Yes
Cables included	AC, HDMI
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	-20 - 60%
Storage temperature (T-T)	20 - 80 °C
Storage relative humidity (H-H)	10 - 90%
Certificates	
Certification	FCC, CE, LVD, UKCA, WEEE, RoHS, REACH, EAC, ICES-003(Issue 7)
Network	
Ethernet LAN	Yes
Wi-Fi	No
Technical details	
Compliance certificates	CE, Low Voltage Directive (LVD), REACH, RoHS, WEEE

USB playback	Yes
--------------	-----

Other features

Cable lock slot type	Kensington
----------------------	------------

Matmenys ir svoris

Matmenys (I × P × A)	14,00cm × 106,00cm × 67,00cm
----------------------	------------------------------

Svoris	11,00kg
--------	---------