



Asrock Phantom Gaming B850 Riptide WiFi AMD B850 Socket AM5 ATX

Modelis: B850 RIPTIDE WIFI

Gamintojas: ASROCK

EAN: 4711581490079

Prekės kodas: 365283

212.98€

Certification: FCC, CE, ErP/EuP | Maximum internal memory: 256 GB | S/PDIF out port: Yes | Product colour: Black | Supported storage drive interfaces: PCI Express 4.0, PCI Express 5.0, SATA III | Motherboard chipset: AMD B850 | Bluetooth: Yes | Audio output channels: 7.1 channels | Audio chip: Realtek ALC4082 | LAN controller: Killer E3100G | Supported storage drive types: HDD & SSD | RAID levels: 0 | Motherboard chipset family: AMD | CPU fan connector: Yes | Unbuffered memory: Yes | RAID levels: 1 | RAID levels: 10 | BIOS type: UEFI AMI | 2nd M.2 highest PCI Express generation: 4.0 | 3rd M.2 largest key size: 2280 | RAID support: Yes | Maximum resolution: 3840 x 2160 pixels | Warnings: Dispose of in accordance with local regulations for electronic waste. | Number of EPS power connectors (8-pin): 2 | Warnings: Do not disassemble to avoid damage to internal components and loss of warranty. | Number of SATA III connectors: 4 | Number of chassis fan connectors: 3 | 4th M.2 largest key size: 2280 | Ethernet LAN (RJ-45) ports: 1 | USB 2.0 ports quantity: 4 | USB connector type: USB Type-C | Front panel audio connector: Yes | 3rd M.2 highest PCI Express generation: 4.0 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Motherboard form factor: ATX | Warnings: Avoid contact with liquids to prevent electronic damage. | 2nd M.2 largest key size: 2280 | 4th M.2 highest PCI Express generation: 4.0 | USB 2.0 connectors: 2 | Parallel processing technology support: Not supported | ECC compatibility: ECC & Non-ECC | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 2 | USB connector type: USB Type-A | HDCP: Yes | Number of M.2 (M) slots: 4 | ATX Power connector (24-pin): Yes | 1st M.2 largest key size: 2280 | USB 3.2 Gen 2x2 connectors: 1 | 1st M.2 highest PCI Express generation: 5.0 | Number of water pump connectors: 1 | Number of CPU fan connectors: 2 | Number of RGB LED pin headers: 1 | Wi-Fi: Yes | Headphone outputs: 2 | TPM connector: Yes | USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity: 2 | Ethernet LAN: Yes | EPS power connector (8-pin): Yes | Memory channels: Dual-channel | RGB LED pin header: Yes | HDMI version: 2.1 | Windows operating systems supported: Windows 11 x64 | Width: 305 mm | Line-in: Yes | Wi-Fi standards: 802.11g | Memory slots type: DIMM | HDMI ports quantity: 1 | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Microphone in: Yes | 12V power connector: Yes | Supported processor sockets: Socket AM5 | PCI Express x16 (Gen 4.x) slots: 1 | Wi-Fi standards: 802.11b | Wi-Fi standards: Wi-Fi 6E (802.11ax) | Ethernet interface type: 2.5 Gigabit Ethernet | Top Wi-Fi standard: Wi-Fi 7 (802.11be) | Bluetooth version: 5.4 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 3 | Windows operating systems supported: Windows 10 x64 | PCI Express x16 (Gen 5.x) slots: 1 | Wi-Fi-AP antenna jack: 2 | Depth: 244 mm | Wi-Fi standards: Wi-Fi 4 (802.11n) | Supported memory types: DDR5-SDRAM | Antenna included: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: Wi-Fi 7 (802.11be) | Number of storage drives supported: 8 | Processor socket: Socket AM5 | Cables included: SATA | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 2 | Number of memory slots: 4 | Compatible processor series: AMD Ryzen 7000 Series | Processor manufacturer: AMD | Compatible processor series: AMD Ryzen 9000 Series | Compatible processor series: AMD Ryzen 8000 Series