



ASUS PRIME B760-PLUS D4 Intel B760 LGA 1700 ATX

Modelis: 90MB1CW0-M1EAY0

Gamintojas: ASUS

EAN: 4711081970309

Prekės kodas: 365292

116.99€

Ethernet LAN (RJ-45) ports: 1 | Motherboard form factor: ATX | Number of M.2 (E) slots: 1 | RAID levels: 1 | EPS power connector (8-pin): Yes | DisplayPorts quantity: 1 | CPU fan connector: Yes | Headphone outputs: 1 | USB 2.0 connectors: 2 | PCI Express x16 (Gen 4.x) slots: 1 | Power source type: ATX | Processor socket: LGA 1700 | Cooling type: Passive | Wi-Fi: No | Memory slots type: DIMM | Number of M.2 (M) slots: 3 | Supported memory types: DDR4-SDRAM | Front panel audio connector: Yes | RAID levels: 0 | Ethernet interface type: 2.5 Gigabit Ethernet | HDMI ports quantity: 1 | Number of COM connectors: 1 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Package weight: 1.16 kg | PCI Express x1 (Gen 3.x) slots: 2 | RAID levels: 10 | Number of storage drives supported: 7 | Number of SATA III connectors: 4 | Thunderbolt headers: 1 | Width: 305 mm | Audio output channels: 7.1 channels | Windows operating systems supported: Windows 10 | RAID levels: 5 | Supported processor sockets: LGA 1700 | DisplayPort version: 1.4 | VGA (D-Sub) ports quantity: 1 | Number of memory slots: 4 | TPM connector: Yes | Number of chassis fan connectors: 3 | ATX Power connector (24-pin): Yes | Package height: 53 mm | Motherboard chipset family: Intel | 12V power connector: Yes | RAID support: Yes | Package width: 328 mm | Parallel processing technology support: Not

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

supported | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 2 | Front panel connector: Yes | Package depth: 266 mm | User guide: Yes | Ethernet LAN: Yes | Peripheral (Molex) power connectors (4-pin): 1 | Memory channels: Dual-channel | Depth: 244 mm | Windows operating systems supported: Windows 11 | Cables included: SATA | Maximum number of SMP processors: 1 | BIOS type: UEFI AMI | USB 2.0 ports quantity: 2 | Line-in: Yes | Compatible processor series: Intel® Core™ i5 | Compatible processor series: Intel® Celeron® | Processor manufacturer: Intel | HDMI version: 2.1 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 2 | Compatible processor series: Intel® Core™ i7 | Compatible processor series: Intel® Core™ i9 | Compatible processor series: Intel® Pentium® Gold | Supported storage drive interfaces: M.2, SATA III | Compatible processor series: Intel® Core™ i3 | Warnings: Do not dispose of the motherboard in the ordinary rubbish bin the product requires special disposal. | Warnings: Avoid direct contact with electronics to prevent electrostatic damage. | Warnings: Before starting any maintenance or installation, disconnect the product from the power supply. | RGB LED pin header: Yes | Number of HDDs supported: 4 | USB 3.2 Gen 2x2 Type-C ports quantity: 1 | ECC compatibility: Non-ECC | PCI Express x16 (Gen 5.x) slots: 1 | Supported memory clock speed (max): 5066 MHz | Motherboard chipset: Intel B760 | S/PDIF out connector: Yes | Supported storage drive types: HDD & SSD | Unbuffered memory: Yes | Supported memory clock speeds: 3466 | Supported memory clock speeds: 4000 | Supported memory clock speeds: 4800 MHz | Supported memory clock speeds: 3733 | Supported memory clock speeds: 4400 | Supported memory clock speeds: 5000 | Supported memory clock speeds: 4600 | Supported memory clock speeds: 2400 | Supported memory clock speeds: 2800 | Supported memory clock speeds: 5066 | Supported memory clock speeds: 3000 | Supported memory clock speeds: 3200 MHz | Supported memory clock speeds: 2666 | Supported memory clock speeds: 4266 | Supported memory clock speeds: 3333 | Supported memory clock speeds: 3400 | Maximum internal memory: 128 GB | Supported memory clock speeds: 2133 | Supported memory clock speeds: 2933 | Supported memory clock speeds: 3600