



ASUS PRIME B760M-A D4- CSM Intel B760 LGA 1700 micro ATX

Modelis: 90MB1D00-M1EAYC

Gamintojas: ASUS

EAN: 4711081984061

Prekės kodas: 365296

112.99€

Microphone in: Yes | Memory slots type: DIMM | Compatible processor series: Intel® Core™ i5 | Compatible processor series: Intel® Celeron® | 12V power connector: Yes | Ethernet LAN: Yes | PCI Express x16 (Gen 4.x) slots: 3 | Depth: 244 mm | Width: 244 mm | Ethernet interface type: 2.5 Gigabit Ethernet | Supported memory types: DDR4-SDRAM | Headphone outputs: 3 | Compatible processor series: Intel® Core™ i3 | Compatible processor series: Intel® Core™ i7 | Compatible processor series: Intel® Core™ i9 | Compatible processor series: Intel® Pentium® Gold | RGB LED pin header: Yes | Wi-Fi: No | Number of storage drives supported: 6 | Processor socket: LGA 1700 | Supported memory clock speed (max): 5333 MHz | Number of memory slots: 4 | ECC compatibility: Non-ECC | RAID support: Yes | Motherboard chipset: Intel B760 | S/PDIF out connector: Yes | PCI Express x1 (Gen 3.x) slots: 1 | Supported storage drive interfaces: M.2, SATA III | Supported memory clock speeds: 3000 | Supported memory clock speeds: 5333 MHz | TPM connector: Yes | EPS power connector (8-pin): Yes | Memory channels: Dual-channel | Supported memory clock speeds: 2133 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

DisplayPorts quantity: 1 | Motherboard chipset family: Intel | DisplayPort version: 1.4 | Motherboard form factor: micro ATX | Supported memory clock speeds: 3466 | Supported processor sockets: LGA 1700 | Supported memory clock speeds: 3733 | Supported memory clock speeds: 4400 | Supported memory clock speeds: 5000 | Supported memory clock speeds: 3400 | Maximum internal memory: 128 GB | Audio output channels: 7.1 channels | Number of chassis fan connectors: 2 | Supported memory clock speeds: 2400 | Supported memory clock speeds: 2800 | Supported memory clock speeds: 5066 | Supported memory clock speeds: 3333 | ATX Power connector (24-pin): Yes | Windows operating systems supported: Windows 11 | Cables included: SATA | HDMI version: 2.1 | Windows operating systems supported: Windows 10 x64 | Supported memory clock speeds: 4600 | HDMI ports quantity: 2 | Supported memory clock speeds: 4000 | Supported memory clock speeds: 4800 | RAID levels: 0 | RAID levels: 10 | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 2 | Number of SATA III connectors: 4 | RAID levels: 5 | Supported memory clock speeds: 3200 | Supported memory clock speeds: 2666 | Supported memory clock speeds: 4266 | Supported memory clock speeds: 2933 | Supported memory clock speeds: 3600 | Front panel audio connector: Yes | CPU fan connector: Yes | Ethernet LAN (RJ-45) ports: 1 | Number of COM connectors: 1 | Number of M.2 (M) slots: 2 | BIOS type: UEFI AMI | RAID levels: 1 | Parallel processing technology support: Not supported | USB 2.0 connectors: 2 | Unbuffered memory: Yes | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 3 | Supported storage drive types: HDD & SSD | PS/2 ports quantity: 1 | Processor manufacturer: Intel | USB 2.0 ports quantity: 4

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903