ASUS PRIME H610M-A WIFI D4 Intel H610 LGA 1700 „micro ATX“

Gamintojas: **ASUS** · Modelis: **90MB1C80-M0EAY0** · EAN: **4711081758211** · Prekės kodas: **365301**



101,89 €

Kaina su PVM

Be PVM: **84,21 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Intel LGA 1700 „Intel® Celeron®“, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, „Intel® Pentium®“, Intel® Pentium® Gold
- ✓ PC „micro ATX“ Intel H610 7.1 kanalai
- ✓ DDR4-SDRAM 2 DIMM Maksimali vidinė atmintis: 64 GB
- ✓ HDD & SSD M.2, SATA Palaikomų saugojimo tvarkyklių skaičius: 6
- ✓ BIOS tipas: UEFI AMI 128 Mbit
- ✓ Gigabitinis eternetas „Wi-Fi“ Wi-Fi 5 (802.11ac) Bluetooth 5.0








Aprašymas

ASUS Prime series motherboards are expertly engineered to unleash the full potential of 12th Generation Intel® processors. Boasting a robust power design, comprehensive cooling solutions and intelligent tuning options, Prime H610 provides users and PC DIY builders a range of performance tuning options via intuitive software and firmware features.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

FLEXIBILITY

Comprehensive controls form the foundation of the ASUS Prime series. The Prime H610 motherboard packs flexible tools to tune every aspect of your system, enabling performance tweaks to perfectly match the way you work to maximize productivity.

All-Around Energy Efficiency

The Energy Processing Unit (EPU) automatically optimizes power consumption and maximizes energy savings with Away mode — a smart setting that creates an extreme energy-saving scenario by shutting down unused I/O controllers.

Flexible cooling controls

Prime 600 Series motherboards offer comprehensive control over system fans, via the included Fan Xpert 2+ software. Auto-Tuning mode intelligently configures all parameters with a single click.

Precise Digital Power Control

The Digi+ voltage-regulator module (VRM) delivers real-time control over voltage droop, automatically switching frequency and power-efficiency settings. It also allows you to fine-tune your CPU for ultimate stability and performance.
* Specifications vary by models.

UEFI BIOS

The renowned ASUS UEFI BIOS provides everything you need to configure, tweak and tune your system. It offers intelligently simplified options for PC DIY beginners, as well as comprehensive features for seasoned veterans.

Advanced Tuning for Serious Tweakers

An intuitive Advanced mode offered via the UEFI lets you take complete control. A built-in search feature makes it easy to find options, and various advanced functions let you intelligently make nuanced adjustments so you can dial in performance just the way you want.

Quick and Simple Setup

EZ mode displays vital settings and stats and also offers guided wizards, drag-and-drop functionality, and one-click application of important settings — all to help you get your rig up and running in no time.

Intuitive Graphical Fan Control

Fine-tune individual fan settings simply by dragging a curve with the mouse.

EZ XMP

Improve DRAM performance with one click.

Aura On/Off Mode (Stealth)

Easily enable or disable Aura RGB lighting or every onboard LED, for a subdued aesthetic touch.

COOLING

Prime H610 series are engineered with multiple onboard heatsinks and an array of hybrid fan headers to ensure your rig stays cool and stable under intense workloads.

Heatsinks

VRM Heatsink and Thermal Pad

VRM heatsink and thermal pad improve heat transfer from the MOSFETs and chokes for better cooling performance.

Cooler by Design

Prime H610 series feature comprehensive cooling controls that are configurable via Fan Xpert 2+ software or via the UEFI BIOS.

PERFORMANCE

Prime H610 series are built to handle the additional cores and increased bandwidth of 12th Generation Intel® processors. ASUS H610 motherboards provide all the fundamentals to boost daily productivity, so your system will be ready for action with stable power, intuitive cooling and flexible transfer options.

Storage
Dual M.2 slots (up to 32 Gbps)
Prime H610M-A WIFI D4 offers two M.2 slots that support data-transfer speeds of up to 32 Gbps via PCIe 3.0, enabling quicker boot-up and app load times with OS or application drives.
* Actual transmission speeds will be lower than the theoretical maximum speed.

Connectivity

PCIe® 4.0

Prime H610 motherboards are designed specifically for 12th Generation Intel® Core™ CPUs and offer PCIe® 4.0 connectivity for the latest GPUs. The wide bandwidth and superfast transmission speeds allow you to create feature-rich builds that can handle high loads effortlessly.

USB 3.2 Gen 2 ports

Numerous USB ports support high-end rigs loaded with peripherals, including rear-panel USB Type-A ports with fast USB 3.2 Gen 2 for transmission speeds of up to 10 Gbps.

Wi-Fi 5

PRIME H610M-A WIFI D4 has 802.11ac Wi-Fi with 1x1 2.4/5GHz antennas for up to 433.3Mbps* transfer speeds to ensure that every connected user experiences the best wireless and online speeds!
*Actual speed varies, and depends on networking conditions.

Intel® 1 Gb Ethernet

Intel® Ethernet Connection I219-V reduces CPU overhead and offers exceptionally high TCP and UDP throughput for faster, smoother data transfer.

Personalization

Aura Sync
Outshine the Competition
A well-tuned enthusiast system deserves a matching aesthetic. ASUS Aura offers full RGB lighting control with a variety of functional presets for the built-in RGB LEDs as well as strips and devices connected to the onboard RGB headers — and it can all be synced with an ever-growing portfolio of Aura-capable hardware.

Addressable Gen 2 Headers

Three addressable Gen 2 headers are capable of detecting the number of LEDs on second-gen addressable RGB devices, allowing the software to automatically tailor lighting effects to specific devices. The new headers also offer backward-compatibility with existing Aura RGB gear.

Armoury Crate

Armoury Crate is a new software utility designed to give you centralized control of supported products. From a single intuitive interface, Armoury Crate allows you to easily customize RGB lighting and effects for every compatible device in your arsenal. The software also provides control of settings for an ever-growing number of ASUS products, including keyboard and mouse preferences. Armoury Crate even features dedicated product registration and news to help you stay in touch with the ASUS community.

DIY Friendly

Q-LED Core

The Q-LED Core display produces light patterns by power LED during the Power-On Self-Test (POST) that can help users troubleshoot potential issues.

Fortified PCIe slot prevents damage

SafeSlot Core is the ASUS-exclusive PCIe slot. Featuring a fortified design that's anchored to the motherboard by a special hook, SafeSlot Core provides 1.6x stronger retention and 1.3x greater shearing resistance than standard expansion slots.

Overvoltage Protection
World-class circuit-protecting power design
An exclusive circuit design with built-in voltage regulators to protect your motherboard from damage caused by unexpected high-level voltages from unstable or inferior power supplies.

DRAM Overcurrent Protection
Short-circuit damage prevention
Onboard resettable fuses prevent overcurrent and short-circuit damage. This extends beyond I/O ports to DRAM to safeguard the lifespan of your system and connected devices.

Stainless-Steel Back I/O
3X corrosion-resistance for greater durability
Corrosion-resistant stainless-steel back I/O panels bonded with chromium oxide have a lifespan that's three times longer than ordinary panels.

LANGuard
Pumped-up throughput 2.5X higher surge tolerance
ASUS LANGuard is a hardware-level network protection feature that integrates advanced signal-coupling technology and premium anti-EMI surface-mounted capacitors to improve throughput and ensure a more reliable connection.

Techninė specifikacija

Procesorius	
Procesoriaus gamintojas	Intel
Procesoriaus lizdas	LGA 1700
Procesorių suderinamumas	„Intel® Celeron®“, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, „Intel® Pentium®“, Intel® Pentium® Gold
Maksimalus SMP procesorių skaičius	1
Atmintis	
Palaikomi atminties tipai	DDR4-SDRAM

Atminties angų skaičius	2
Maksimali vidinė atmintis	64 GB
Atminties angų tipas	DIMM
Atminties kanalai	Dviejų kanalų
ECC suderinamumas	Ne-ECC
Palaikomi atminties laikrodžio greičiai	2133,2400,2666,2800,2933,3000,3200 MHz
Nebuferizuota atmintis	Taip
Duomenų laikymo valdikliai	
Palaikomi saugojimo kaupiklių sąsajos	M.2, SATA
Palaikomi saugojimo kaupiklių tipai	HDD & SSD
Palaikomų saugojimo tvarkyklių skaičius	6
Grafika	
Palaikomų ekranų skaičius	3
Vidinis I/O	
USB 2.0 jungtys	2
USB 3.2 (3.1 1 kart.) jungtys	1
USB 3.2 (3.1 2 kart.) jungtys	0
SATA III jungčių skaičius	4
S/PDIF out jungtis	Taip
Priekinio skydelio audio jungtis	Taip
ATX maitinimo jungtis	Taip
CPU fan jungtis	Taip
Šasi fenų jungčių skaičius	2
EPS maitinimo jungtis (8-kaisčiai)	Taip
COM jungčių skaičius	1
TPM jungtis	Taip
12 V maitinimo jungtis	Taip
RGB LED kontaktų pagrindas	Taip
Galinė panelė I/O jungtys	
USB 2.0 portų kiekis	4
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	2
USB 3.2 (3.1 1 kart.) C tipo prievadų skaičius	0
USB 3.2 2 kart. (3.1 2 kart.) A tipo prievadų skaičius	0
USB 3.2 2 kart. (3.1 2 kart.) C tipo prievadų skaičius	0

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Ethernet LAN (RJ-45) portų kiekis	1
VGA (D-Sub) portų kiekis	1
HDMI portų kiekis	1
DVI-D prievadų skaičius	0
PS/2 portų kiekis	2
HDMI versija	2.1
„DisplayPort“ kiekis	1
„DisplayPort“ versija	1.4
Ausinių išvestys	1
Mikrofonas, line-in jack	Taip

Tinklas

„Wi-Fi“	Taip
Ethernet LAN jungtis	Taip
Eterneto sąsajos tipas	Gigabitinis eternetas
„Wi-Fi“ standartas	Wi-Fi 5 (802.11ac)
Wi-Fi standartai	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Bluetooth	Taip
Bluetooth versija	5.0

Savybės

Taikoma	PC
Motininės plokštės formos faktorius	„micro ATX“
Motininės plokštės sisteminio valdiklio šeima	Intel
Pagrindinės plokštės lustas	Intel H610
Garso išvesties kanalai	7.1 kanalai
Palaikomos „Windows“ operacinės sistemos	Windows 10 x64, Windows 11 x64

Plėtotės lizdas

PCI „Express“ x1 (3.x kart.) angos	1
„PCI Express x16“ (4 kartos) lizdai	1
M.2 (M) angų skaičius	2

BIOS

BIOS tipas	UEFI AMI
BIOS atminties dydis	128 Mbit

Logistikos duomenys

Darniosios sistemos (DS) kodas	84733020

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Svoris ir matmenys	
Plotis	244 mm
Ilgis	211 mm
Aukštis	58 mm
Pakuotės turinys	
Pridėti kabeliai	SATA
Tvarkyklės įskaitytos	Taip
Kitos savybės	
Svoris	815 g
Matmenys ir svoris	
Matmenys (I × P × A)	7,00cm × 27,00cm × 27,00cm
Svoris	1,05kg

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

ASUSTeK Computer Inc
Li-Te Road 15, 112 Taipei, TW
asus.com

ATSAKINGAS ASMUO ES

ASUS France S.A.R.L.
Allee bienvenue 10, 93160 Paris, FR
channel.asus.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.